

Safety Data Sheet

according to UK REACH Regulations SI 2020/1577



Revision date: 1/18/2022
Supersedes: 9/30/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier:

Product trade name: Kalama* C-12 Lauric Aldehyde
Company product number: C12ABTW
UK REACH registration number: UK-01-0552317523-9-0003
Substance name: Dodecanal
Substance identification number: EC 203-983-6
Other means of identification: Lauryl aldehyde

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Uses: Fragrance ingredient. Odour agent. See Annex for covered uses.
Uses advised against: None identified

1.3. Details of the supplier of the safety data sheet:

Manufacturer/Supplier: Emerald Kalama Chemical Limited
Dans Road
Widnes, Cheshire WA8 0RF
United Kingdom
Telephone: +44 (0) 151 423 8000
For further information about this SDS: Email: product.compliance@emeraldmaterials.com

1.4. Emergency telephone number:

ChemTel (24 hours): 1-800-255-3924 (USA); +1-813-248-0585 (outside USA).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture:

Product classification according to GB CLP as amended:

Skin Irritation, category 2, H315
Skin sensitizer, category 1B, H317
Eye Irritation, category 2, H319
See Section 2.2 for full text of H (Hazard) statements.

2.2. Label elements:

Product labeling according to GB CLP as amended:

Hazard pictogram(s):



Signal word:

Warning

Hazard statements:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P280 Wear protective gloves/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

SDS Name: Kalama* C-12 Lauric Aldehyde

P362+P364 Take off contaminated clothing and wash it before reuse.

Supplemental information: No Additional Information

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS) - Annex III and GB CLP Guidance on Labelling and Packaging. Regulations in individual countries/regions may determine which statements are required on the product label. See product label for specifics.

2.3. Other hazards:

PBT/vPvB criteria:

This product does not meet the PBT and vPvB classification criteria.

Other hazards:

No Additional Information

See Section 11 for toxicological information.

SECTION 3: Composition/information on ingredients

3.1. Substance:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Weight%</u>	<u>Classification</u>	<u>H Statements</u>
0000112-54-9	Dodecanal	98-100	Eye Irrit. 2- Skin Irrit. 2- Skin Sens. 1B	H315-317-319
0000112-53-8	Dodecan-1-ol	0.1-<1.0	Aquatic Acute 1- Aquatic Chronic 2- Eye Irrit. 2	H319-400-411
<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Weight%</u>	<u>UK REACH Registration No.</u>	<u>EC/List Number</u>
0000112-54-9	Dodecanal	98-100	UK-01-0552317523-9-0003	203-983-6
0000112-53-8	Dodecan-1-ol	0.1-<1.0	Impurity	203-982-0

See Section 16 for full text of H (Hazard) statements.

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

SECTION 4: First aid measures

4.1. Description of first aid measures:

General: If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician/get medical attention.

Eye contact: Immediately flush eyes with plenty of clean water for an extended time, not less than fifteen (15) minutes. Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. If eye irritation persists: Get medical advice/attention.

Skin contact: Immediately remove contaminated clothing and shoes. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. If skin irritation occurs: Get medical advice/attention.

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse out the mouth with water. Get medical attention immediately.

Protection of first aid responders: Wear proper personal protective clothing and equipment.

4.2. Most important symptoms and effects, both acute and delayed:

Irritation. Preexisting sensitization, skin and/or respiratory disorders or diseases may be aggravated. See section 11 for additional information.

4.3. Indication of any immediate medical attention and special treatment needed:

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media:

Suitable: Use water spray, ABC dry chemical, foam or carbon dioxide. Water or foam may cause frothing. Use water to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures.

Unsuitable: Do not use direct water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture:

Unusual fire/explosion hazards: Product is not considered a fire hazard, but will burn if ignited. Closed container may rupture (due to build up in pressure) when exposed to extreme heat. Combustion hazard: waste soaked with this product may heat to temperatures causing self-ignition if improperly discarded. Many aldehydes readily oxidize exothermically when

SDS Name: Kalama* C-12 Lauric Aldehyde

exposed to air. Any clean up materials, like rags, towels, etc. should be washed with water with mild soap or laundered with mild detergent before proper disposal to avoid the potential temperature rise from oxidation.

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (10.6 Hazardous decomposition products) for additional information.

5.3. Advice for firefighters:

Wear self-contained breathing apparatus (SCBA) equipped with a full facepiece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations.

See section 9 for additional information.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures:

See Section 8 for recommendations on the use of personal protective equipment. If spilled in an enclosed area, ventilate. Eliminate ignition sources. Personal Protective Equipment must be worn.

6.2. Environmental precautions:

Do not flush liquid into public sewer, water systems or surface waters.

6.3. Methods and material for containment and cleaning up:

Contain by diking with sand, earth or other non-combustible material. Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse. Combustion hazard: waste soaked with this product may heat to temperatures causing self-ignition if improperly discarded. Immediately after use, rags, steel wool or other waste should be wetted or cleaned with water with mild soap or laundered with mild detergent or placed into a water-filled metal container before proper disposal.

6.4. References to other sections:

See Section 8 for recommendations on the use of personal protection and Section 13 for waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling:

As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Provide eyewash fountains and safety showers in the work area.

7.2. Conditions for safe storage, including any incompatibilities:

Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning. Empty container contains residual product which may exhibit hazards of product. Product can easily oxidize. It is recommended that opened containers be padded with nitrogen. Protect from light.

7.3. Specific end use(s):

Further information concerning special risk management measures: see annex of this safety data sheet (exposure scenarios).

SECTION 8: Exposure controls / personal protection

8.1. Control parameters:

Occupational exposure limits (OEL):

<u>Chemical Name</u>	<u>ACGIH - TWA/Ceiling</u>	<u>ACGIH - STEL</u>
Dodecanal	N/E	N/E
Dodecan-1-ol	N/E	N/E
<u>Chemical Name</u>	<u>UK WEL</u>	
Dodecanal	N/E	
Dodecan-1-ol	N/E	

N/E=Not established (no exposure limits established for the listed substances for listed country/region/organization).

Derived No Effect Levels (DNELs):

Dodecanal

Population

Route

		<u>Acute (local)</u>	<u>Acute (systemic)</u>	<u>Long Term (local)</u>	<u>Long Term (systemic)</u>
Workers	Inhalation	N/E	N/E	0,57 µg/cm2	49,7 mg/m3
Workers	Dermal	N/E	N/E	N/E	14,1 mg/kg bw/day
General population	Inhalation	N/E	N/E	N/E	12,3 mg/m3
General population	Dermal	N/E	N/E	0,28 µg/cm2	7 mg/kg bw/day
General population	Oral	N/E	N/E	N/E	7 mg/kg bw/day
<u>Dodecan-1-ol</u>					
<u>Population</u>	<u>Route</u>	<u>Acute (local)</u>	<u>Acute (systemic)</u>	<u>Long Term (local)</u>	<u>Long Term (systemic)</u>
Workers	Inhalation	N/E	220 mg/m3	N/E	220 mg/m3
Workers	Dermal	N/E	125 mg/kg bw/day	N/E	125 mg/kg bw/day

Predicted No Effect Concentration (PNECs):

Dodecanal

<u>Compartment</u>	<u>PNEC</u>
Freshwater	0,0035 mg/L
Freshwater sediment	1,41 mg/kg dw (0.306 mg/kg ww)
Marine water	0,00035 mg/L
Marine water sediment	0,141 mg/kg dw (0.0306 mg/kg ww)
Intermittent releases	0,035 mg/L
Soil	0,278 mg/kg dw (0.246 mg/kg ww)
STP	10 mg/L
Oral	313 mg/kg food

Dodecan-1-ol

<u>Compartment</u>	<u>PNEC</u>
Freshwater	0,0028 mg/L
Freshwater sediment	1,1 mg/kg dw
Marine water	0,00028 mg/L
Marine water sediment	0,11 mg/kg dw
Soil	0,888 mg/kg dw
STP	0,021 mg/L

N/E=Not established; N/A=Not applicable (not required); bw=body weight; dw=dry weight; ww=wet weight.

8.2. Exposure controls:

Appropriate engineering controls: Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.

Individual protection measures, such as personal protective equipment:

Eye/face protection: Safety glasses or goggles required.

Hand protection: Avoid skin contact when mixing or handling the material by wearing impervious and chemical resistant gloves. In case of prolonged immersion or frequently repeated contact, gloves with breakthrough times greater than 480 minutes (protection class 6) are recommended. For brief contact or splash applications, gloves with breakthrough times of 30 minutes or greater are recommended (protection class 2 or greater). The protective gloves to be used must comply with the specifications of the standard EN 374. Suitability and durability of a glove is dependent on usage (e.g. frequency and duration of contact, other chemicals which may be handled, chemical resistance of glove material and dexterity). Always seek advice of the glove supplier as to the most suitable glove material.

Skin and body protection: Use good laboratory/workplace procedures including personal protective clothing: labcoat, safety glasses and protective gloves.

Respiratory protection: Respiratory protection is not needed with proper ventilation. Wear an approved respirator (e.g., an organic vapor respirator, a full face air purifying respirator for organic vapors, or a self-contained breathing apparatus) whenever exposure to aerosol, mist, spray, fume or vapor exceed the applicable exposure limit(s) of any chemical substance listed in this SDS.

Further information: Eyewash fountains and safety showers are recommended in the work area.

Environmental exposure controls: See Sections 6 and 12.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties:

Appearance:	Liquid. Colorless to pale yellow
Odour:	Aldehyde-like
Odour threshold:	Not Available
pH:	Not Available
Melting point/Freezing point:	12.5 °C (54.5 °F)
Initial boiling point and boiling range °C:	239 °C
Initial boiling point and boiling range °F:	462 °F
Flash point:	>110 °C (>230 °F) Setaflash (Closed Tester)
Evaporation rate:	Not Available

SDS Name: Kalama* C-12 Lauric Aldehyde

Flammability (solid, gas):	Not Applicable (liquid)
Upper/lower flammability or explosive limits:	LFL/LEL: Not Available UFL/UEL: Not Available
Vapour pressure:	0.7 Pa @ 20°C
Vapour density:	Not Available
Relative density:	0.827-0.835 @ 20°C
Solubility in water:	1.6 mg/L @ 20°C
Partition coefficient (n-octanol/water):	4.9 (OECD 117)
Autoignition temperature:	205 °C (401 °F)
Decomposition temperature:	Not Available
Viscosity:	3.9 mm ² /s @ 20°C; 2.5 mm ² /s @ 40°C
Explosive properties:	Not explosive
Oxidising properties:	Not oxidizing
% Volatile By weight:	100%
VOC:	Not Available
Surface tension:	63.9 mN/m @ 20°C (0.274 mg/L)

9.2. Other information:

Amounts specified are typical and do not represent a specification.

SECTION 10: Stability and reactivity

10.1. Reactivity:

Presents no significant reactivity hazard. Neither pyrophoric nor reactive with water. Does not form explosive mixtures with other organic materials.

10.2. Chemical stability:

This product is stable. Normally stable even at elevated temperatures and pressures. Does not undergo explosive decomposition; is shock stable; and is not an oxygen donor.

10.3. Possibility of hazardous reactions:

Hazardous polymerization will not occur.

10.4. Conditions to avoid:

Excessive heat and ignition sources.

10.5. Incompatible materials:

Avoid strong acids, bases, and oxidizing agents. Avoid contact with reducing agents.

10.6. Hazardous decomposition products:

Carbon dioxide, carbon monoxide and hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects:

Information on likely routes of exposure:

General: Caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure.

Eyes: Causes serious eye irritation.

Skin: May cause allergic skin reaction. Causes skin irritation.

Inhalation: High airborne concentrations of vapors resulting from heating, misting or spraying may cause irritation of the respiratory tract and mucous membranes.

Ingestion: Ingestion may cause irritation.

Acute toxicity information: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Inhalation LC50</u>	<u>Species</u>	<u>Oral LD50</u>	<u>Species</u>	<u>Dermal LD50</u>	<u>Species</u>
Dodecanal	N/E	N/E	23100 mg/kg	Rat/ adult	>2000 mg/kg	Rabbit/ adult
Dodecan-1-ol	>71 mg/L (1 hour, similar materials)	Rat/ adult	>2000 mg/kg	Rat/ adult	>2000 mg/kg	Rabbit/ adult

Skin corrosion/irritation: Causes skin irritation - Category 2.

SDS Name: Kalama* C-12 Lauric Aldehyde

Chemical Name

Dodecanal
Dodecan-1-ol

Skin irritation

Irritant
Mild irritant

Species

Similar materials
Human

Serious eye damage/irritation: Causes serious eye irritation - Category 2.

Chemical Name

Dodecanal
Dodecan-1-ol

Eye irritation

Irritant
Irritant (OECD 405)

Species

Similar materials
Rabbit/ adult

Respiratory or skin sensitization: Skin sensitization - Category 1B.

Chemical Name

Dodecanal
Dodecan-1-ol

Skin sensitisation

Sensitizer (EC3 6.8%)
Non-sensitizer

Species

Mouse/Local lymph node assay (similar materials)
Guinea Pig/ adult

Carcinogenicity: Not classified (no relevant information found).

Germ cell mutagenicity: Not classified (based on available data, the classification criteria are not met). DODECANAL - READ-ACROSS: Mutagenicity was negative in in-vivo genotoxicity assays. Mixed results were seen in in-vitro genotoxicity assays.

Reproductive toxicity: Not classified (based on available data, the classification criteria are not met). DODECANAL - READ-ACROSS/WEIGHT OF EVIDENCE: Reproductive toxicity, oral study in rats: NOAEL (no-observed adverse-effect-level) of 200-300 mg/kg bw/day.

Specific target organ toxicity (STOT) - single exposure: Not classified (based on available data, the classification criteria are not met).

Specific target organ toxicity (STOT) - repeated exposure: Not classified (based on available data, the classification criteria are not met). DODECANAL: Repeated dose study, oral, rat: NOAEL (no-observed-adverse-effect-level) =1409.7 mg/kg bw/day.

Aspiration hazard: Not classified (based on available data, the classification criteria are not met).

Other toxicity information: No additional information available.

SECTION 12: Ecological information

12.1. Toxicity:

DODECANAL: This substance showed no toxicity to fish, algae or invertebrates at the solubility limit.

Chemical Name	Species	Acute	Acute	Chronic
Dodecanal	Fish	LC50 2.6 mg/L (96 hours) (>water solubility)	N/E	N/E
Dodecanal	Invertebrates	EC50 >0.48 mg/L (48 hours) (>water solubility)	N/E	N/E
Dodecanal	Algae	EC50 >0.35 mg/L (72 hours) (>water solubility)	N/E	NOEC >0.35 mg/L(72 hours) (>water solubility)
Dodecanal	Micro-organisms	EC0 >16 mg/L (16 hours)		
Dodecan-1-ol	Fish	LC50 1.01 mg/L (96 hours)	N/E	N/E
Dodecan-1-ol	Invertebrates	EC50 0.765 mg/L (48 hours)	N/E	NOEC 0.014 mg/L (21 days)
Dodecan-1-ol	Algae	EC50 0.66 mg/L (72 hours)	N/E	NOEC 0.085 mg/L(72 hours)

12.2. Persistence and degradability:

Chemical Name

Dodecanal
Dodecan-1-ol

Biodegradation

Readily biodegradable (OECD 301F)
Readily biodegradable (OECD 301D)

12.3. Bioaccumulative potential:

Chemical Name

Dodecanal
Dodecan-1-ol

Bioconcentration Factor (BCF)

34-711 L/kg
N/E

Log Kow

4.9 (OECD 117)
5.4 @ 23°C

12.4. Mobility in soil:

Chemical Name

Dodecanal
Dodecan-1-ol

Mobility in soil (Koc/Kow)

3981 (OECD 121)
17980 (calculated)

12.5. Results of PBT and vPvB assessment:

This product does not meet the PBT and vPvB classification criteria.

12.6. Other adverse effects:

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods:

SDS Name: Kalama* C-12 Lauric Aldehyde

Dispose of unused contents (incineration) in accordance with national and local regulations. Dispose of container in accordance with national and local regulations. Ensure the use of properly authorized waste management companies, where appropriate.

See Section 8 for recommendations on the use of personal protective equipment.

SECTION 14: Transport information

The information below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions.

14.1. UN number: N/A

14.2. UN proper shipping name:

Not regulated - See Bill of Lading for Details

14.3. Transport hazard class(es):

U.S. DOT hazard class: N/A

Canada TDG hazard class: N/A

Europe ADR/RID hazard class: N/A

IMDG Code (ocean) hazard class: N/A

ICAO/IATA (air) hazard class: N/A

A "N/A" listing for the hazard class indicates the product is not regulated for transport by that regulation.

14.4. Packing group: N/A

14.5. Environmental hazards:

Marine pollutant: Not Applicable

Hazardous substance (USA): Not Applicable

14.6. Special precautions for user:

Not Applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code:

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

STATUTORY INSTRUMENTS 2020 No. 1577, The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 [UK REACH]: Applicable components have been registered, are exempt or otherwise compliant. UK REACH is only relevant to substances either manufactured or imported into the UK. Emerald Kalama Chemical has met its obligations under the UK REACH regulation. UK REACH information regarding this product is provided for informational purposes only. Each Legal Entity may have differing UK REACH obligations, depending on their place in the supply chain. Emerald's compliance with UK REACH does not imply automatic coverage for Downstream Users located in the UK. For material manufactured outside of the UK, the importer of record must understand and meet their specific obligations under the regulation.

UK Authorizations and/or restrictions on use: Not Applicable

Other UK information: No Additional Information

Chemical inventories:

<u>Regulation</u>	<u>Status</u>
Australian Inventory of Industrial Chemicals (AIIC):	Y
Canadian Domestic Substances List (DSL):	N
Canadian Non-Domestic Substances List (NDSL):	Y
China Inventory of Existing Chemical Substances (IECSC):	Y
European EC Inventory (EINECS, ELINCS, NLP):	Y
Japan Existing and New Chemical Substances (ENCS):	Y
Japan Industrial Safety and Health Law (ISHL):	Y
Korean Existing and Evaluated Chemical Substances (KECL):	Y
New Zealand Inventory of Chemicals (NZIoC):	Y
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Y
Taiwan Inventory of Existing Chemicals:	Y
U.S. Toxic Substances Control Act (TSCA) (Active):	Y

A "Y" listing indicates all intentionally added components are either listed or are otherwise compliant with the regulation. A "N" listing indicates that for one or more components: 1) there is no listing on the public inventory (or is not on the ACTIVE inventory for U.S. TSCA); 2) no information is available; or 3) the component has not been reviewed. A "Y" for New Zealand may mean that a qualified group standard may exist for the components in this product.

Europe REACH (EC) 1907/2006: Applicable components are registered, exempt or otherwise compliant. EU REACH is only

SDS Name: Kalama* C-12 Lauric Aldehyde

relevant to substances either manufactured or imported into the EU. Emerald Kalama Chemical has met its obligations under the EU REACH regulation. EU REACH information regarding this product is provided for informational purposes only. Each Legal Entity may have differing EU REACH obligations, depending on their place in the supply chain. Emerald's compliance with EU REACH does not imply automatic coverage for Downstream Users located in the EU. For material manufactured outside of the EU, the importer of record must understand and meet their specific obligations under the regulation.

15.2. Chemical safety assessment:

A chemical safety assessment has been carried out for the substance or mixture consistent with the EU REACH regulation.

SECTION 16: Other information

Hazard (H) Statements in the Composition section (Section 3):

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Reason for revision: Changes in Section(s): 1

Evaluation method For classification Of mixtures: Not Applicable (substance)

Legend:

* : Trademark owned by Emerald Kalama Chemical, LLC.

ACGIH: American Conference of Governmental Industrial Hygienists

ATE: Acute toxicity estimate

N/A: Not Applicable

N/E: None Established

STEL: Short Term Exposure Limit

TWA: Time Weighted Average (exposure for 8-hour workday)

UK WEL: United Kingdom Workplace Exposure Limits

Users Responsibility/Disclaimer of Liability:

The information set forth herein is based on our current knowledge, and is intended to describe the product solely with respect to health, safety and the environment. As such, it must not be interpreted as a guarantee of any specific property of the product. As a result, the customer shall be solely responsible for deciding whether said information is suitable and beneficial.

Safety Data Sheet Preparer:

Product Compliance Department

Emerald Kalama Chemical, LLC

1499 SE Tech Center Place, Suite 300

Vancouver, WA 98683

United States

Annex

Exposure Scenarios

Substance information:

Name of substance: Dodecanal.

EC# 203-983-6 / CAS# 112-54-9

UK REACH Registration number: UK-01-0552317523-9-0003

EU REACH Registration number: 01-2119969441-33-0004

List of exposure scenarios:

ES1: Formulation - Formulation of fragrance compounds

ES2: Formulation - Formulation of fragranced end-products

ES3: Use at industrial sites - Industrial end-use of fragranced end-products

ES4: Use by professional workers - Professional end-use of fragranced end products

ES5: Consumer use - Consumer end-use of fragranced end products

General remarks:

This product is a liquid fragrance ingredient used in a wide variety of fragranced end-products, including washing, cleaning and cosmetic products. It functions as an odour agent. Formulated fragranced products for industrial, professional and consumer uses contain less than 1%. The neat substance is mixed with other fragrance ingredients to form a fragrance compound (compounding) followed by the formulation of the compound into a fragranced end-product (formulation).

Reference: IFRA REACH Exposure scenarios for Fragrance Substances. Version 2.1/11 December 2012.

Exposure scenario (1): Formulation - Formulation of fragrance compounds

1. Exposure scenario (1)

Short title of the exposure scenario:

Formulation - Formulation of fragrance compounds

List of use descriptors:

Process category (PROC): PROC1, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC15

SDS Name: Kalama* C-12 Lauric Aldehyde

Environmental release category (ERC): ERC2 (SpERC IFRA 2.1a.v1, 2.1b.v1)

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition.

PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.

PROC15 Use as laboratory reagent. Use of substances at small scale laboratory (< 1 l or 1 kg present at workplace).

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

SpERC IFRA 2.1(a): Formulation of fragrance compounds at large/medium sites; SpERC IFRA 2.1(b): Formulation of fragrance compounds at small sites.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see <http://www.cefic.org/Industry-support/Implementing-reach/Libraries/>.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Generally accepted standards of occupational hygiene are maintained. Smoking, eating and drinking are prohibited at the workplace. Spills are cleaned immediately.

Product characteristics:

Concentration of substance:

- PROC1, PROC3, PROC5, PROC8b: >25%

- PROC8a, PROC9, PROC15: 5-25%

Concentration of substance in compounds: The weight fraction of fragrance substances in compounds is highly variable and may be as high as 20% w/w (IFRA 2012). A reasonable maximum concentration of this substance in fragrance compounds is 1,14%.

Physical state: liquid.

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Workers may handle amounts of fragrance substance in the kg-range per day.

Frequency and duration of use/exposure:

Duration:

- PROC3, PROC5, PROC8a: 1-4 hours/day.

- PROC1, PROC8b, PROC9: 15 minutes-1 hour/day.

- PROC15: <15 minutes.

Frequency: <=220 days/year.

Human factors not influenced by risk management:

ECETOC developed values for typically affected skin surface areas for each process category which vary from 240 to 1980 cm².

Other given operational conditions affecting workers exposure:

Location: Indoor use.

Domain: Industrial use.

Technical conditions and measures to control dispersion from source towards the worker:

General ventilation: Basic general ventilation (1-3 air changes per hour): 0%.

Containment:

- PROC1: Closed system (minimal contact during routine operations).

- PROC3: Closed batch process with occasional controlled exposure.

- PROC8b, PROC9: Semi-closed process with occasional controlled exposure.

- PROC5, PROC8a, PROC15: No.

Local exhaust ventilation: Not required.

Occupational Health and Safety Management System: Advanced.

Organisational measures to prevent/limit releases, dispersion and exposure:

Avoiding frequent and direct contact with substance. Minimisation of manual phases. Regular cleaning of equipment and work area. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Conditions and measures related to personal protection, hygiene and health evaluation:

Respiratory protection: Not required.

Chemical safety goggles recommended.

Dermal protection:

- PROC1, PROC3, PROC9, PROC15: No (Effectiveness Dermal: 0%).

- PROC5, PROC8a, PROC8b: Yes (chemically resistant gloves conforming to EN374 with basic employee training) (Effectiveness Dermal: 80%).

Additional good practice advice:

Generally accepted standards of occupational hygiene are maintained.

Minimisation of manual phases/work tasks.

Minimisation of splashes and spills.

Avoidance of contact with contaminated tools and objects.

Regular cleaning of equipment and work area.

Training staff on good practice.

Management/supervision in place to check that RMMs in place are being used correctly and OCs followed.

2.2 Control of environmental exposure

General:

Environmental release may vary depending on the size of the compounding site according to IFRA guideline (2012). It is not more than 0.5% of the use volume for smaller compounding sites, whereas for large/medium sites it is not more than 0.2%. The size of compounding sites was defined using data obtained in a questionnaire: small sites produce less than 1000 tonnes of compounds per year, medium sites produce between 1000 and 10,000 tonnes of compounds per year and large sites produce more than 10,000 tonnes of compounds per year (RIFM 2009).

Product characteristics:

Concentration of substance in compounds: The weight fraction of fragrance substances in compounds is highly variable and may be as high as 20% w/w (IFRA 2012). A reasonable maximum concentration of this substance in fragrance compounds is 1,14%.

Physical state: liquid.

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Maximum annual use at a site: 50 tons/year.

Percentage of tonnage used at regional scale: 10 %.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (freshwater); >=198,000 m3/day (seawater).

Other given operational conditions affecting environmental exposure:

Indoor use.

Industrial use.

Release fraction to air from process: 0,025. Local release rate: 10 kg/day (ERC2).

Release fraction to wastewater from process: 0.002 (large/medium site); 0.005 (small site). Local release rate: 0,8 kg/day (ERC2).

Release fraction to soil from process: 0 (ERC2).

Technical conditions and measures at process level (source) to prevent release:

Sites have impermeable floors.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Do not apply industrial sludge to natural soils.

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (freshwater).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Health: ECETOC TRA Worker v3. Only highest figures are presented here.

Assessment method-Environment: EUSES 2.1.2.

Health

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Worker, long-term, systemic, Dermal	4,11 mg/kg bw/day	0,29	PROC9
Worker, long-term, systemic, Inhalation	27,65 mg/m3	0,56	PROC8a
Worker, long-term, systemic, Combined routes	N/A	0,67	PROC8a

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,00331 mg/L	0,946	
Freshwater sediment	0,289 mg/kg ww	0,944	
Marine water	0,000330 mg/L	0,943	
Marine water sediment	0,0288 mg/kg ww	0,941	
Soil	0,000241 mg/kg ww	0,00098	
STP	0,0324 mg/L	0,00324	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

Notes: The exposure scenario categories consist of a number of activities. An individual worker may conduct one or several of these activities during one shift and a specific PROC or PROCs have been identified as worst-case activities for combined exposure. If parts of the worker's shift are spent conducting PROCs other than the worst-case PROC activities, the daily exposure of this worker will be lower than estimated for the worst case.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Health:

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Indoor use, without LEV, no respirator required. Dermal protection: PROC1, PROC3, PROC9, PROC15: No (Effectiveness Dermal: 0%). PROC5, PROC8a, PROC8b: Yes (chemically resistant gloves conforming to EN374 with basic employee training) (Effectiveness Dermal: 80%). Concentration of substance: PROC1, PROC3, PROC5, PROC8b: >25%. PROC8a, PROC9, PROC15: 5-25%.

SDS Name: Kalama* C-12 Lauric Aldehyde

Environment: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (2): Formulation - Formulation of fragranced end-products

1. Exposure scenario (2)

Short title of the exposure scenario:

Formulation - Formulation of fragranced end-products

List of use descriptors:

Product category (PC): PC3, PC8, PC28, PC31, PC35, PC39

Process category (PROC): PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

Environmental release category (ERC): ERC2 (SpERC AISE and Cosmetics Europe (CE)).

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition.

PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.

PROC14 Tableting, compression, extrusion, pelletisation, granulation. This covers processing of mixtures and/or substances into a defined shape for further use.

PROC15 Use as laboratory reagent. Use of substances at small scale laboratory (< 1 l or 1 kg present at workplace).

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

SpERC:

- IFRA SG-1: AISE Granular and low viscosity liquids (large site)(AISE 2.1.a,g).

- IFRA SG-2: AISE Granular and low viscosity liquids (medium site)(AISE 2.1.b,h).

- IFRA SG-3: AISE Granular and low viscosity liquids (small site)(AISE 2.1.c,i).

- IFRA SG-4: AISE High viscosity liquids+CE/AISE Solid products+CE Low viscosity liquids (large site)(AISE 2.1.j+CE/AISE 2.3.a+CE2.1.a).

- IFRA SG-5: AISE High viscosity liquids+CE/AISE Solid products+CE Low viscosity liquids (medium site)(AISE 2.1.k+CE/AISE 2.3.b+CE2.1.b).

- IFRA SG-6: AISE High viscosity liquids+CE/AISE Solid products+CE Low viscosity liquids (small site)(AISE 2.1.l+CE/AISE 2.3.c+CE2.1.c).

- IFRA SG-7: AISE + CE Fine fragrances (cleaning with solvent)(large/medium/small site)(CE 2.2a-c).

- IFRA SG-8: ERC2 default (large/medium/small site)(CE 2.1.d-j).

Further explanations:

Fragrance compounds are used by several industries, such as the cosmetics industry or detergents industry, in the formulation of fragranced end-products. The compounds are combined with various other ingredients to make up the final fragranced products, such as washing and cleaning products, air care products, biocides, waxes and polishes and cosmetics.

PC3 Air care products.

PC8 Biocidal products.

PC28 Perfumes, fragrances.

PC31 Polishes and wax blends.

PC35 Washing and cleaning products.

PC39 Cosmetics, personal care products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see <http://www.cefic.org/Industry-support/Implementing-reach/Libraries/>.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Generally accepted standards of occupational hygiene are maintained. Smoking, eating and drinking are prohibited at the workplace. Spills are cleaned immediately.

Product characteristics:

Concentration of substance:

- PROC1, PROC2, PROC3, PROC5, PROC8b, PROC15: 5-25%

- PROC8a, PROC9, PROC14: <1%

Concentration of substance in fragranced end-products: It is anticipated that fragranced products normally will contain less than 1% of an individual fragrance substance (IFRA 2012). Multiplying the maximum concentration of the substance in fragrance compounds by the highest concentration of compounds in fragrance end-products of 1,14% gives a maximum concentration of Dodecanal in fragranced end-products is about 0,07%.

Physical state:

- PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC15: liquid.

- PROC14: solid.

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Workers may handle amounts of fragrance end-product in the kg-range per day.

SDS Name: Kalama* C-12 Lauric Aldehyde

Frequency and duration of use/exposure:

Duration:

- PROC3, PROC5, PROC8a: 1-4 hours/day.
- PROC1, PROC2, PROC8b, PROC9: 15 minutes-1 hour/day.
- PROC14: >4 hours/day.
- PROC15: <15 minutes.

Frequency: <=220 days/year.

Human factors not influenced by risk management:

ECETOC developed values for typically affected skin surface areas for each process category which vary from 240 to 1980 cm².

Other given operational conditions affecting workers exposure:

Location: Indoor use.

Domain: Industrial use.

Technical conditions and measures to control dispersion from source towards the worker:

General ventilation: Basic general ventilation (1-3 air changes per hour): 0%.

Containment:

- PROC1: Closed system (minimal contact during routine operations).
- PROC2: Closed continuous process with occasional controlled exposure.
- PROC3: Closed batch process with occasional controlled exposure.
- PROC8b, PROC9: Semi-closed process with occasional controlled exposure.
- PROC5, PROC8a, PROC14, PROC15: No.

Local exhaust ventilation: Not required.

Occupational Health and Safety Management System: Advanced.

Organisational measures to prevent/limit releases, dispersion and exposure:

Avoiding frequent and direct contact with substance. Minimisation of manual phases. Regular cleaning of equipment and work area. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Conditions and measures related to personal protection, hygiene and health evaluation:

Respiratory protection: Not required.

Chemical safety goggles recommended.

Dermal protection: No (Effectiveness Dermal: 0%).

Additional good practice advice:

Generally accepted standards of occupational hygiene are maintained.

Minimisation of manual phases/work tasks.

Minimisation of splashes and spills.

Avoidance of contact with contaminated tools and objects.

Regular cleaning of equipment and work area.

Training staff on good practice.

Management/supervision in place to check that RMMs in place are being used correctly and OCs followed.

2.2 Control of environmental exposure

Product characteristics:

Concentration of substance in fragranced end-products: It is anticipated that fragranced products normally will contain less than 1% of an individual fragrance substance (IFRA 2012). Multiplying the maximum concentration of the substance in fragrance compounds by the highest concentration of compounds in fragrance end-products of 1,14% gives a maximum concentration of Dodecanal in fragranced end-products is about 0,07%.

Physical state: liquid.

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Amounts used in the EU:

- IFRA SG-1: 37,5 tons/year.
- IFRA SG-2: 14 tons/year.
- IFRA SG-3: 11,5 tons/year.
- IFRA SG-4: 10,5 tons/year.
- IFRA SG-5, IFRA SG-6: 4,5 tons/year.
- IFRA SG-7: 16 tons/year.
- IFRA SG-8: 1,5 tons/year.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m³/day (freshwater); >=198,000 m³/day (seawater).

Other given operational conditions affecting environmental exposure:

Indoor use.

Industrial use.

Release fraction to air from process: 0.

Release fraction to wastewater from process:

- IFRA SG-1: 0,0001.
- IFRA SG-2, SG-4: 0,001.
- IFRA SG-3, SG-5: 0,002.
- IFRA SG-6: 0,004.
- IFRA SG-7: 0.
- IFRA SG-8: 0,02.

Release fraction to soil from process: 0.

Technical conditions and measures at process level (source) to prevent release:

Sites have impermeable floors.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Do not apply industrial sludge to natural soils.

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (freshwater).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Health: ECETOC TRA Worker v3. Only highest figures are presented here.

Assessment method-Environment: EUSES 2.1.2.

Health

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Worker, long-term, systemic, Dermal	8,23 mg/kg bw/day	0,584	PROC5, PROC8b
Worker, long-term, systemic, Inhalation	13,82 mg/m3	0,278	PROC5
Worker, long-term, systemic, Combined routes	N/A	0,862	PROC5

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000576 mg/L	0,165	ERC2 (SG-8)
Freshwater sediment	0,0503 mg/kg ww	0,164	ERC2 (SG-8)
Marine water	0,000056 mg/L	0,160	ERC2 (SG-8)
Marine water sediment	0,00489 mg/kg ww	0,160	ERC2 (SG-8)
Soil	0,0379 mg/kg ww	0,154	ERC2 (SG-8)
STP	0,00486 mg/L	0,000486	ERC2 (SG-8)

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

Notes: The exposure scenario categories consist of a number of activities. An individual worker may conduct one or several of these activities during one shift and a specific PROC or PROCs have been identified as worst-case activities for combined exposure. If parts of the worker's shift are spent conducting PROCs other than the worst-case PROC activities, the daily exposure of this worker will be lower than estimated for the worst case.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES**Health:**

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Indoor use, without LEV, no respirator required. Dermal protection: No (Effectiveness Dermal: 0%). Concentration of substance: PROC1, PROC2, PROC3, PROC5, PROC8b, PROC15: 5-25%. PROC8a, PROC9, PROC14: <1%.

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (3): Use at industrial sites - Industrial end-use of fragranced end-products**1. Exposure scenario (3)****Short title of the exposure scenario:**

Use at industrial sites - Industrial end-use of fragranced end-products

List of use descriptors:

Product category (PC): PC3, PC8, PC28, PC31, PC35, PC39

Process category (PROC): PROC1, PROC2, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

Environmental release category (ERC): ERC4 (SpERC AISE 4.1.v.1)

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC4 Chemical production where opportunity for exposure arises.

PROC7 Industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.

PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.

PROC13 Treatment of articles by dipping and pouring.

Name of contributing environmental scenario and corresponding ERCs:

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article).

SpERC AISE 4.1.v.1: Industrial Use of Water Borne Processing Aids.

Further explanations:

SDS Name: Kalama* C-12 Lauric Aldehyde

Industrial use of Laundry products:

- CS1 Laundry detergent: Automatic process (PROC2, PROC8a, PROC8b).
- CS2 Conditioner (softener/starch): Automatic process (PROC2, PROC8a, PROC8b).
- CS3 Laundry aid (gasing): Automatic process (PROC2, PROC8a, PROC8b).
- CS4 Laundry aid (non-gasing): Automatic process (PROC2, PROC8a, PROC8b).

Industrial use of Vehicle cleaning Products:

- CS5 Train cleaner: Semi-Automatic process (PROC4, PROC8a, PROC8b).
- CS6 Aeroplane cleaner: Semi-Automatic process (PROC4, PROC8a, PROC8b).
- CS7 Car wash product: Semi-Automatic process (PROC4, PROC8a, PROC8b).
- CS8 Car wash product: Spray and rinse process (PROC7, PROC8a, PROC8b).
- CS9 Car wash product: Spray and wipe manual process (PROC7, PROC8a, PROC8b, PROC10)
- CS10 Dewaxing product: Semi-Automatic process (PROC4, PROC8a, PROC8b).
- CS11 Boat cleaning: Semi-Automatic process (PROC8a, PROC8b, PROC10).
- CS12 Boat cleaning: Spray and wipe manual process (PROC7, PROC8a, PROC8b).

Industrial use of Food beverage and pharmacos products:

- CS13 Food process cleaner: Cleaning In Place process (PROC1, PROC8a, PROC8b).
- CS14 Food process cleaner: Semi closed cleaning process (PROC4, PROC8a, PROC8b).
- CS15 Chain maintenance product: Automatic spray process (PROC7, PROC8a, PROC8b).
- CS16 Chain maintenance product: Automatic drip and brush process (PROC13).
- CS17 Defoaming product: Automatic process (PROC1, PROC8a, PROC8b).
- CS18 Foam cleaner: Semi-Automatic with venting process (PROC7, PROC8a, PROC8b).
- CS19 Foam cleaner: Semi-Automatic without venting process (PROC7, PROC8a, PROC8b).
- CS20 Animal housing care: Semi-Automatic process (PROC7, PROC8a, PROC8b).
- CS21 Disinfection product: Semi-Automatic process (PROC4, PROC8a, PROC8b).
- CS22 Disinfection product: Fogging and gassing Semi-automatic process (PROC7, PROC8a, PROC8b).

Industrial use of Water treatment products:

- CS23 Preservation and sanitation agent: drink and pool water: (PROC4, PROC8a, PROC8b).
- CS24 Preservation and sanitation agent: waste water: (PROC4, PROC8a, PROC8b).

Industrial Use of Facade/surface Cleaning Products:

- CS25 Facade/surface cleaner: High pressure process (PROC4, PROC8a, PROC8b).
- CS26 Facade/surface cleaner: Medium pressure process (PROC4, PROC8a, PROC8b).

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see <http://www.cefic.org/Industry-support/Implementing-reach/Libraries/>.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Generally accepted standards of occupational hygiene are maintained. Smoking, eating and drinking are prohibited at the workplace. Spills are cleaned immediately.

Product characteristics:

Concentration of substance: <1%.

Concentration of substance in fragranced end-products: It is anticipated that fragranced products normally will contain less than 1% of an individual fragrance substance (IFRA 2012). Multiplying the maximum concentration of the substance in fragrance compounds by the highest concentration of compounds in fragrance end-products of 1,14% gives a maximum concentration of Dodecanal in fragranced end-products is about 0,07%.

Physical state: liquid (PROC1, PROC2, PROC4, PROC7, PROC10, PROC13); liquid and solid (PROC8a, PROC8b).

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Workers may handle amounts of fragrance end-product in the kg-range per day.

Frequency and duration of use/exposure:

Duration:

- PROC1, PROC2, PROC4 (CS5-CS7, CS10, CS14, CS23-CS26), PROC7 (CS15, CS18-CS20, CS22), PROC10, PROC13: >4 hours.
- PROC4 (CS21): 1-4 hours.
- PROC7 (CS8, CS9, CS12), PROC8a/PROC8b (CS5-CS12, CS18-CS22): 15 minutes-1 hour.
- PROC8a/PROC8b (CS1-CS4, CS13-CS15, CS17, CS23-CS26): <15 minutes.

Frequency: <=240 days/year.

Human factors not influenced by risk management:

ECETOC developed values for typically affected skin surface areas for each process category which vary from 240 to 1980 cm².

Other given operational conditions affecting workers exposure:

Location: Unless otherwise stated, Indoor use.

- PROC4 (CS23-CS26), PROC7 (CS9, CS12), PROC8a/PROC8b (CS9, CS11, CS12, CS23-CS26), PROC10: Outdoor use.

Domain: Industrial use.

Technical conditions and measures to control dispersion from source towards the worker:

General ventilation: Unless otherwise stated, Basic general ventilation (1-3 air changes per hour): 0%.

- PROC4 (CS23-CS26), PROC7 (CS9, CS12), PROC8a/PROC8b (CS9, CS11, CS12, CS23-CS26), PROC10: Not relevant.

Local exhaust ventilation: Unless otherwise stated, Not required.

- PROC13: Yes (90% effectiveness).

- PROC7 (CS18), PROC8a/PROC8b (CS18): Yes (95% effectiveness).

Occupational Health and Safety Management System: Advanced.

Organisational measures to prevent/limit releases, dispersion and exposure:

Avoiding frequent and direct contact with substance. Minimisation of manual phases. Regular cleaning of equipment and work area. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Conditions and measures related to personal protection, hygiene and health evaluation:

Respiratory protection: Unless otherwise stated, Not required.

- PROC4 (CS25, CS26), PROC7 (CS15, CS19, CS20, CS22): Yes (mimimum efficiency inhalation: 90%).

Chemical safety goggles recommended.

Dermal protection: Unless otherwise stated, No (Effectiveness Dermal: 0%).

- PROC4 (CS10, CS14, CS25, CS26), PROC7, PROC8a/PROC8b (CS1-CS15, CS17-CS19, CS22-CS26), PROC10, PROC13: Yes (chemically resistant gloves conforming to EN374) (Effectiveness Dermal: 80%).

Additional good practice advice:

Generally accepted standards of occupational hygiene are maintained.

Minimisation of manual phases/work tasks.

Minimisation of splashes and spills.

Avoidance of contact with contaminated tools and objects.

Regular cleaning of equipment and work area.

Training staff on good practice.

Management/supervision in place to check that RMMs in place are being used correctly and OCs followed.

2.2 Control of environmental exposure

General:

Industrial use is considered as wide dispersive use together with the other end-uses of fragranced products. Industrial end-use products are similar to those used by professionals and consumers and releases will be to the waste water stream (IFRA 2012).

Product characteristics:

Concentration of substance in fragranced end-products: It is anticipated that fragranced products normally will contain less than 1% of an individual fragrance substance (IFRA 2012). Multiplying the maximum concentration of the substance in fragrance compounds by the highest concentration of compounds in fragrance end-products of 1,14% gives a maximum concentration of Dodecanal in fragranced end-products is about 0,07%.

Physical state: liquid.

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Daily wide dispersive use: 254,5 kg/day.

Amounts used in the EU: 92892 kg/year.

Fraction of regional tonnage used locally: 0.00075.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (freshwater); >=198,000 m3/day (seawater).

Other given operational conditions affecting environmental exposure:

Industrial use.

Release fraction to air from process: 0.

Release fraction to wastewater from process: 1.0. Local release rate: 0,191 kg/day (SpERC AISE 4.1.v1)

Release fraction to soil from process: 0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Do not apply industrial sludge to natural soils.

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (freshwater).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Health: ECETOC TRA Worker v3. Only highest figures are presented here.

Assessment method-Environment: EUSES 2.1.2.

Health

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Worker, long-term, systemic, Dermal	1,37 mg/kg bw/day	0,0973	PROC8a/PROC8b (CS20, CS21)
Worker, long-term, systemic, Inhalation	15,36 mg/m3	0,3091	PROC7 (CS8)
Worker, long-term, systemic, Combined routes	N/A	0,3698	PROC7 (CS8)

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000862 mg/L	0,246	
Freshwater sediment	0,0804 mg/kg ww	0,263	
Marine water	0,0000846 mg/L	0,242	
Marine water sediment	0,0076 mg/kg ww	0,248	
Soil	0,0603 mg/kg ww	0,245	
STP	0,00773 mg/L	0,000773	

SDS Name: Kalama* C-12 Lauric Aldehyde

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

Notes: The exposure scenario categories consist of a number of activities. An individual worker may conduct one or several of these activities during one shift and a specific PROC or PROCs have been identified as worst-case activities for combined exposure. If parts of the worker's shift are spent conducting PROCs other than the worst-case PROC activities, the daily exposure of this worker will be lower than estimated for the worst case.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES	
Health:	Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Indoor/outdoor use, PROC7 (CS18), PROC8a/PROC8b (CS18), PROC13: LEV used, PROC4 (CS10, CS14, CS25, CS26), PROC7, PROC8a/PROC8b (CS1-CS15, CS17-CS19, CS22-CS26), PROC10, PROC13: with gloves. Respiratory protection: PROC4 (CS25, CS26), PROC7 (CS15, CS19, CS20, CS22): Yes (minimum efficiency inhalation: 90%). Concentration of substance: <1%.
Environment:	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (4): Use by professional workers - Professional end-use of fragranced end products
1. Exposure scenario (4)

Short title of the exposure scenario:
Use by professional workers - Professional end-use of fragranced end products

List of use descriptors:

Product category (PC): PC3, PC8, PC28, PC31, PC35, PC39
Process category (PROC): PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13
Environmental release category (ERC): ERC8a, ERC8d (SpERC AISE and Cosmetics Europe (CE)).

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.
PROC4 Chemical production where opportunity for exposure arises.
PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.
PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.
PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.
PROC11 Non industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.
PROC13 Treatment of articles by dipping and pouring.

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).
ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor).

Further explanations:

Professional Use of Laundry products:

- CS1 Laundry detergent: Semi-automatic process (PROC1, PROC8a, PROC8b).
- CS2 Laundry detergent: Manual process (PROC8a, PROC8b, PROC10).
- CS3 Conditioner (softener/starch): Semi-automatic process (PROC1, PROC8a, PROC8b).
- CS4 Laundry aid (gasing): Semi-automatic process (PROC1, PROC8a, PROC8b).
- CS5 Laundry aid (non-gasing): Semi-automatic process (PROC1, PROC8a, PROC8b).
- CS6 Laundry aid (non-gasing): Manual process (PROC4, PROC8a, PROC8b).
- CS7 Prespotter/Stain remover: Manual process (PROC10, PROC11).

Professional Use of Dishwash products:

- CS8 Dishwash product: Manual process (PROC8a, PROC8b, PROC10).
- CS9 Rinse aid: Automatic process (PROC2, PROC8a, PROC8b).
- CS10 Dishwash product: Semi-automatic process (PROC1, PROC8a, PROC8b).
- CS11 Rinse aid: Semi-automatic process (PROC1, PROC8a, PROC8b).

Professional Use of General surface cleaning products:

- CS12 General purpose cleaner: Manual process (PROC8a, PROC8b, PROC10).
- CS13 General purpose cleaner: Spray and wipe manual process (PROC8a, PROC8b, PROC10, PROC11).
- CS14 Kitchen cleaner: Manual process (PROC8a, PROC8b, PROC10).
- CS15 Kitchen cleaner: Spray and wipe manual process (PROC8a, PROC8b, PROC10, PROC11).
- CS16 Sanitary cleaner: Manual process (PROC8a, PROC8b, PROC10).
- CS17 Sanitary cleaner: Spray and wipe manual process (PROC8a, PROC8b, PROC10, PROC11).
- CS18 Descaling agent: Manual process (PROC10).
- CS19 Descaling agent: Spray and rinse manual process (PROC8a, PROC8b, PROC10, PROC11).
- CS20 General surface cleaning: Dipping process: (PROC8a, PROC8b, PROC13).
- CS21 Oven/Grill cleaner: Manual process (PROC10).
- CS22 Oven/Grill Cleaner: Spray and wipe manual process (PROC10, PROC11).
- CS23 Glass cleaner: Manual process (PROC8a, PROC8b, PROC10).
- CS24 Glass cleaner: Spray and wipe manual process (PROC10, PROC11).
- CS25 Surface disinfectant: Manual process (PROC8a, PROC8b, PROC10).
- CS26 Surface disinfectant: Spray and rinse manual process (PROC8a, PROC8b, PROC10, PROC11).
- CS27 Metal cleaning agent: Manual process (PROC10).
- CS28 Surface cleaning: Wet wipes manual process (PROC10).

SDS Name: Kalama* C-12 Lauric Aldehyde

Professional Use of Floor care products:

- CS29 Floor cleaner: Semi-Automatic process (PROC8a, PROC8b, PROC10).
- CS30 Floor cleaner: Spray and wipe manual process (PROC8a, PROC8b, PROC10, PROC11).
- CS31 Floor cleaner: Manual process (PROC8a, PROC8b, PROC10).
- CS32 Floor stripper: Manual process (PROC8a, PROC8b, PROC10).
- CS33 Floor stripper: Semi-Automatic process (PROC8a, PROC8b, PROC10).
- CS34 Carpet cleaner: Manual process (PROC8a, PROC8b, PROC10).
- CS35 Carpet cleaner: Semi-Automatic process (PROC8a, PROC8b, PROC10).
- CS36 Carpet cleaner: Prespotter, brush manual process (PROC10, PROC11).

Professional Use of Maintenance Products :

- CS37 Drain unblocker: Manual process (PROC13).
- CS38 Drain cleaner: Manual process (PROC13).

Professional Use of Vehicle cleaning Products:

- CS39 Car wash product: Semi-Automatic process (PROC4, PROC8a, PROC8b).
- CS40 Car wash product: Spray manual process (PROC8a, PROC8b, PROC11).
- CS41 Car wash product: Spray and wipe manual process (PROC8a, PROC8b, PROC10, PROC11).
- CS42 Dewaxing product: Semi-Automatic process (PROC4, PROC8a, PROC8b).
- CS43 Boat cleaner: Manual process (PROC8a, PROC8b, PROC10).
- CS44 Boat cleaner: Spray and wipe manual process (PROC8a, PROC8b, PROC10, PROC11).

Professional Use of Food beverage and pharmacos products:

- CS45 Animal housing care: Manual process (PROC8a, PROC8b, PROC10).

Professional Use of Facade/surface Cleaning Products:

- CS46 Facade/surface cleaner: High pressure process (PROC8a, PROC8b, PROC11).
- CS47 Facade/surface cleaner: Medium pressure process (PROC8a, PROC8b, PROC10, PROC11).

Professional Use of Medical Devices:

- CS48 Medical devices: Semi-automatic process (PROC1, PROC8a, PROC8b).
- CS49 Medical devices: Dipping process (PROC8a, PROC8b, PROC13).
- CS50 Medical devices: Manual process (PROC8a, PROC8b, PROC10).
- CS51 Medical devices: Spray and wipe manual process (PROC8a, PROC8b, PROC10, PROC11).

Professional Use of Polish products:

- CS1POLISH Floor polish, impregnation: Manual process (PROC10).
- CS2POLISH Floor polish, impregnation: Semi-Automatic process (PROC10).
- CS3POLISH Floor polish, impregnation: Spray and wipe manual process (PROC10, PROC11).
- CS4POLISH Wooden furniture care: Manual process (PROC10).
- CS5POLISH Wooden furniture care: Spray and wipe manual process (PROC10, PROC11).
- CS6POLISH Leather care product: Manual process (PROC10).
- CS7POLISH Leather care product: Spray and wipe manual process (PROC10, PROC11).
- CS8POLISH Leather care product: Semi-automatic process (PROC2, PROC8a, PROC8b).
- CS9POLISH Stainless steel care: Manual process (PROC10).
- CS10POLISH Stainless steel care: Spray and wipe manual process (PROC10, PROC11).

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see <http://www.cefic.org/Industry-support/Implementing-reach/Libraries/>.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Generally accepted standards of occupational hygiene are maintained. Smoking, eating and drinking are prohibited at the workplace. Spills are cleaned immediately.

Product characteristics:

Concentration of substance: <1%.

Concentration of substance in fragranced end-products: It is anticipated that fragranced products normally will contain less than 1% of an individual fragrance substance (IFRA 2012). Multiplying the maximum concentration of the substance in fragrance compounds by the highest concentration of compounds in fragrance end-products of 1,14% gives a maximum concentration of Dodecanal in fragranced end-products is about 0,07%.

Physical state: liquid (PROC1, PROC2, PROC4, PROC10, PROC11, PROC13); liquid and solid (PROC8a, PROC8b).

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Professionals may handle amounts of fragrance end-product in the kg-range per day.

Frequency and duration of use/exposure:

Duration:

- PROC1, PROC2 (CS8POLISH), PROC4 (CS39, CS42), PROC10 (CS7, CS12-CS17, CS19, CS22-CS27, CS29-CS35, CS41, CS43-CS45, CS47, CS50, CS51, CS1POLISH-CS3POLISH, CS9POLISH), PROC11 (CS46): >4 hours.
 - PROC10 (CS2, CS8, CS18, CS28, CS36, CS4POLISH-CS7POLISH, CS10POLISH): 1-4 hours.
 - PROC8a/PROC8b (CS2, CS12-CS17, CS19, CS23, CS25-CS26, CS29-CS35, CS39-CS45, CS50, CS51, CS8POLISH), PROC10 (CS21), PROC11 (CS7, CS13, CS15, CS17, CS19, CS22, CS24, CS26, CS30, CS36, CS40, CS41, CS44, CS47, CS51, CS3POLISH): 15 minutes-1 hour.
 - PROC2 (CS9), PROC4 (CS6), PROC8a/PROC8b (CS1, CS3-CS6, CS8-CS11, CS20, CS46-49), PROC11 (CS5POLISH, CS7POLISH, CS10POLISH), PROC13: <15 minutes.
- Frequency: <=365 days/year.

Human factors not influenced by risk management:

ECETOC developed values for typically affected skin surface areas for each process category which vary from 240 to 1980 cm².

Other given operational conditions affecting workers exposure:

SDS Name: Kalama* C-12 Lauric Aldehyde

Location: Unless otherwise stated, Indoor use.

- PROC8a/PROC8b (CS41, CS43, CS44), PROC10 (CS41, CS43, CS44), PROC11 (CS41, CS44): Outdoor use.

Domain: Professional use.

Technical conditions and measures to control dispersion from source towards the worker:

General ventilation: Unless otherwise stated, Basic general ventilation (1-3 air changes per hour): 0%.

- PROC8a/PROC8b (CS41, CS43, CS44), PROC10 (CS41, CS43, CS44), PROC11 (CS41, CS44): Not relevant.

Local exhaust ventilation: Not required.

Occupational Health and Safety Management System: Basic.

Organisational measures to prevent/limit releases, dispersion and exposure:

Avoiding frequent and direct contact with substance. Minimisation of manual phases. Regular cleaning of equipment and work area. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Conditions and measures related to personal protection, hygiene and health evaluation:

Respiratory protection: Unless otherwise stated, Not required.

- PROC8a/8b (CS46, CS47), PROC10 (CS47), PROC11 (CS46, CS47): Yes (minimum efficiency inhalation: 90%).

Dermal protection: Unless otherwise stated, Yes (chemically resistant gloves conforming to EN374 with basic employee training) (Effectiveness Dermal: 80%).

- PROC1, PROC2, PROC4 (CS39, CS42), PROC8a/PROC8b (CS8, CS12, CS14, CS16, CS23, CS29, CS31, CS34, CS35, CS45), PROC10 (CS2, CS8, CS12, CS14, CS16, CS23, CS25, CS27, CS28, CS29, CS31, CS33-CS35, CS43, CS45, CS50, CS1POLISH, CS2POLISH, CS4POLISH, CS6POLISH, CS9POLISH): No (Effectiveness Dermal: 0%).

Additional good practice advice:

Generally accepted standards of occupational hygiene are maintained.

Minimisation of manual phases/work tasks.

Minimisation of splashes and spills.

Avoidance of contact with contaminated tools and objects.

Regular cleaning of equipment and work area.

Training staff on good practice.

Management/supervision in place to check that RMMs in place are being used correctly and OCs followed.

2.2 Control of environmental exposure

General:

Environmental release due to end-use of fragranced end-products is characterised by the IFRA guideline as wide dispersive use (IFRA 2012). It was assumed that indoor use of fragranced products is likely to generate emissions mainly into the waste water, i.e. the release to waste water was set to 100% and emissions into air or soil were neglected.

Product characteristics:

Concentration of substance in fragranced end-products: It is anticipated that fragranced products normally will contain less than 1% of an individual fragrance substance (IFRA 2012). Multiplying the maximum concentration of the substance in fragrance compounds by the highest concentration of compounds in fragrance end-products of 1,14% gives a maximum concentration of Dodecanal in fragranced end-products is about 0,07%.

Physical state: liquid.

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Daily wide dispersive use: 254,5 kg/day.

Amounts used in the EU: 92892 kg/year.

Fraction of regional tonnage used locally: 0.00075.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (freshwater); >=198,000 m3/day (seawater).

Other given operational conditions affecting environmental exposure:

Indoor/Outdoor use.

Professional use.

Release fraction to air from process: 0.

Release fraction to wastewater from process: 1.0. Local release rate: 0,191 kg/day (IFRA 2012)

Release fraction to soil from process (final release): 0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Do not apply industrial sludge to natural soils.

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (freshwater).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Health: ECETOC TRA Worker v3. Only highest figures are presented here.

Assessment method-Environment: EUSES 2.1.2.

Health

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
--------------------	-----------------------	-----	-------

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Worker, long-term, systemic, Dermal	2,743 mg/kg bw/day	0,195	PROC10
Worker, long-term, systemic, Inhalation	19,20 mg/m ³	0,386	PROC4, PROC10
Worker, long-term, systemic, Combined routes	N/A	0,581	PROC10

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000862 mg/L	0,246	
Freshwater sediment	0,0804 mg/kg ww	0,263	
Marine water	0,0000846 mg/L	0,242	
Marine water sediment	0,0076 mg/kg ww	0,248	
Soil	0,0603 mg/kg ww	0,245	
STP	0,00773 mg/L	0,000773	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

Notes: The exposure scenario categories consist of a number of activities. An individual worker may conduct one or several of these activities during one shift and a specific PROC or PROCs have been identified as worst-case activities for combined exposure. If parts of the worker's shift are spent conducting PROCs other than the worst-case PROC activities, the daily exposure of this worker will be lower than estimated for the worst case.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Health:	Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Indoor/outdoor use, without LEV. Dermal protection: Unless otherwise stated, Yes (chemically resistant gloves conforming to EN374 with basic employee training) (Effectiveness Dermal: 80%). PROC1, PROC2, PROC4 (CS39, CS42), PROC8a/PROC8b (CS8, CS12, CS14, CS16, CS23, CS29, CS31, CS34, CS35, CS45), PROC10 (CS2, CS8, CS12, CS14, CS16, CS23, CS25, CS27, CS28, CS29, CS31, CS33-CS35, CS43, CS45, CS50, CS1POLISH, CS2POLISH, CS4POLISH, CS6POLISH, CS9POLISH): No (Effectiveness Dermal: 0%). Respiratory protection: PROC8a/8b (CS46, CS47), PROC10 (CS47), PROC11 (CS46, CS47): Yes (minimum efficiency inhalation: 90%). Concentration of substance: <1%.
Environment:	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (5): Consumer use - Consumer end-use of fragranced end products**1. Exposure scenario (5)****Short title of the exposure scenario:**

Consumer use - Consumer end-use of fragranced end products

List of use descriptors:

Product category (PC): PC3, PC8, PC28, PC31, PC35, PC39

Environmental release category (ERC): ERC8a, ERC8d (SpERC AISE and Cosmetics Europe (CE)).

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor).

Further explanations:

PC3 Air care products: Air fresheners aerosol (Mini-aerosol, timed release aerosol); Air fresheners non-aerosol (Perfume in/on solid substance (gel), diffusers (heated), candle).

PC8 Biocidal products (e.g. Disinfectants, pest control): Insecticides (liquid electric, spray neat); Repellents.

PC28 Perfumes, fragrances.

PC31 Polishes and wax blends: Furniture floor and leather care (spraying).

PC35 Washing and cleaning products: Laundry regular (powder, liquid); Laundry compact (powder, liquid/gel, tablet); Fabric conditioners (liquid regular, liquid concentrate); Laundry additives (powder bleach, liquid bleach, tablet); Hand dishwashing (liquid regular, liquid concentrate);

Machine dishwashing (powder, liquid, tablet); Laundry aids (ironing aids-starch spray); Surface cleaners (liquid, powder, gel neat; spray neat);

Toilet cleaners (powders, liquid, gel, tablet); Carpet cleaners (liquid, spray, solid); Wipes (bathroom, kitchen, floor); Oven cleaners (trigger spray).

PC39 Cosmetics, personal care products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure**2.1 Control of consumer exposure****General:**

PC28 & PC39: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation.

Product characteristics:

Concentration of substance in fragranced end-products: The weight fraction of an individual fragrance substance in fragranced products used by consumers is anticipated to be below 1% (IFRA 2012) except for air fresheners where pure fragrance compounds containing up to 5% of an individual substance may be put in a diffuser.

Concentration of substance: Unless otherwise stated, covers concentrations up to 0,1%.

- PC3 (Air fresheners aerosol): up to 0,25%.

- PC3 (Air fresheners non-aerosol): up to 5%.

SDS Name: Kalama* C-12 Lauric Aldehyde

- PC8 (Insecticides (liquid electric, spray neat); Repellents): up to 1%.
 - PC35 (Laundry regular, Laundry compact, Laundry additives, Hand dishwashing, Machine dishwashing): up to 0,05%.
 - PC35 (Toilet cleaners): up to 0,3%.
 - PC35 (Laundry aids): up to 0,025%.
- Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Consumers may use amounts of fragrance end-product in the gram-range per day.

Frequency and duration of use/exposure:

Frequency and duration of use: Consumers usually use fragranced end-products for a short duration, e.g. 20 minutes for a liquid all-purpose cleaner. The frequency of use depends on the product. While for example dishwashing products are used on a daily basis, all-purpose cleaners are generally used on 104 days per year, i.e. every third day (RIVM 2006).

Other given operational conditions affecting consumers exposure:

Body weight: 60 kg.

Inhalation exposure model - The size of the room where the fragranced product is used depends on the application field of the fragranced product.

Inhalation rate: 20 m3/day.

Conditions and measures related to personal protection and hygiene:

Consumers are not expected to use specific personal protection during the use of fragranced products.

2.2 Control of environmental exposure

General:

Environmental release due to end-use of fragranced end-products is characterised by the IFRA guideline as wide dispersive use (IFRA 2012). It was assumed that indoor use of fragranced products is likely to generate emissions mainly into the waste water, i.e. the release to waste water was set to 100% and emissions into air or soil were neglected.

Product characteristics:

Concentration of substance in fragranced end-products: It is anticipated that fragranced products normally will contain less than 1% of an individual fragrance substance (IFRA 2012). Multiplying the maximum concentration of the substance in fragrance compounds by the highest concentration of compounds in fragrance end-products of 1,14% gives a maximum concentration of Dodecanal in fragranced end-products is about 0,07%.

Physical state: liquid.

Vapour pressure: 0,7 Pa at 20°C.

Amounts used:

Daily wide dispersive use: 254,5 kg/day.

Amounts used in the EU: 92892 kg/year.

Fraction of the main local source: 0.00075.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (freshwater); >=198,000 m3/day (seawater).

Other given operational conditions affecting environmental exposure:

Indoor/Outdoor use.

Consumer use.

Release fraction to air from process: 0.

Release fraction to wastewater from process: 1.0. Local release rate: 0,191 kg/day (IFRA 2012)

Release fraction to soil from process (final release): 0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Do not apply industrial sludge to natural soils.

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (freshwater).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Health: AISE REACT Consumer Tool and ConsExpo Tool. Only highest figures are presented here.

Assessment method-Environment: EUSES 2.1.2.

Health

<u>Effect/Compartment</u>	<u>Exposure estimate/PEC</u>	<u>RCR</u>	<u>Notes</u>
Consumer, long-term, systemic, Dermal	0,923 mg/kg bw/day	0,132	PC8 (Repellents)
Consumer, long-term, systemic, Inhalation	0,0447 mg/m3	0,00363	PC8 (Insecticides), PC3 (Air fresheners, aerosol)
Consumer, long-term, systemic, Oral	0,000002 mg/kg bw/day	0,000000354	PC35 (Hand dishwashing, Machine dishwashing)
Consumer, long-term, systemic, Combined routes	N/A	0,132	PC8 (Repellents)

Environment

<u>Effect/Compartment</u>	<u>Exposure estimate/PEC</u>	<u>RCR</u>	<u>Notes</u>
---------------------------	------------------------------	------------	--------------

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000862 mg/L	0,246	
Freshwater sediment	0,0804mg/kg ww	0,263	
Marine water	0,0000846 mg/L	0,242	
Marine water sediment	0,0076 mg/kg ww	0,248	
Soil	0,0603 mg/kg ww	0,245	
STP	0,00773 mg/L	0,000773	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Health:	Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
Environment:	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.