

Safety Data Sheet

according to Regulation (EC) 1907/2006 (REACH)



Revision date: 1/20/2022
Supersedes date: 10/18/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier:

Product trade name: Kalama* Vetimoss
Company product number: VETIMOSS
REACH registration number: 01-2120866299-37-0000
Substance name: 2-tert-Butyl-1,4-dimethoxybenzene
Substance identification number: EC 244-216-5
Other means of identification: 32186; Benzene, 2-(1,1-dimethylethyl)-1,4-dimethoxy-

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Uses: Fragrance ingredient. Industrial applications. Professional applications.
Consumer applications. See Annex for covered uses.
Uses advised against: None identified

1.3. Details of the supplier of the safety data sheet:

Manufacturer/Supplier: Emerald Kalama Chemical Limited
Dans Road
Widnes, Cheshire WA8 0RF
United Kingdom
Telephone: +44 (0) 151 423 8000
EU Only Representative: Penman Consulting bvba
Avenue des Arts 10
B-1210 Brussels
Belgium
Telephone: +32 (0) 2 403 7239
email: pcbvba10@penmanconsulting.com
For further information about this SDS: Email: product.compliance@emeraldmaterials.com

1.4. Emergency telephone number:

ChemTel (24 hours): 1-800-255-3924 (USA); +1-813-248-0585 (outside USA).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture:

Product classification according to Regulation (EC) 1272/2008 (CLP) as amended:

Germ Cell Mutagenicity, category 2, H341
Hazardous to the aquatic environment, Chronic, category 2, H411
See Section 2.2 for full text of H (Hazard) statements (EC 1272/2008).

2.2. Label elements:

Product labeling according to Regulation (EC) 1272/2008 (CLP) as amended:

Hazard pictogram(s):



Signal word:

Warning

Hazard statements:

H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

SDS Name: Kalama* Vetimoss

P308+P313 IF exposed or concerned: Get medical advice/attention.

P391 Collect spillage.

Supplemental information: No Additional Information

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS) - Annex III and ECHA Guidance on Labelling and Packaging. Regulations in individual countries/regions may determine which statements are required on the product label. See product label for specifics.

2.3. Other hazards:

PBT/vPvB criteria: This product does not meet the PBT and vPvB classification criteria.

Endocrine disrupting properties: No specific information available.

Other hazards: No Additional Information

See Section 11 for toxicological information.

SECTION 3: Composition/information on ingredients

3.1. Substance:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Weight%</u>	<u>Classification</u>	<u>H Statements</u>
0021112-37-8	2-tert-Butyl-1,4-dimethoxybenzene	99-100	Aquatic Chronic 2- Muta. 2	H341-411
<u>CAS-No.</u>	<u>Chemical Name</u>	<u>REACH Registration No.</u>	<u>EC/List Number</u>	
0021112-37-8	2-tert-Butyl-1,4-dimethoxybenzene	01-2120866299-37-0000	244-216-5	
<u>CAS-No.</u>	<u>Chemical Name</u>	<u>M-factor</u>	<u>SCLs</u>	<u>ATE</u>
0021112-37-8	2-tert-Butyl-1,4-dimethoxybenzene	N/A	N/E	Not Available

See Section 16 for full text of H (Hazard) statements (EC 1272/2008).

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

SECTION 4: First aid measures

4.1. Description of first aid measures:

General: If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician/get medical attention.

Following eye contact: Immediately flush eyes with plenty of clean water for an extended time, not less than fifteen (15) minutes. Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. If eye irritation persists: Get medical advice/attention.

Following skin contact: Immediately remove contaminated clothing and shoes. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. If skin irritation occurs: Get medical advice/attention.

Following inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Following ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse out the mouth with water. Get medical attention immediately.

Protection of first aid responders: Wear proper personal protective clothing and equipment.

4.2. Most important symptoms and effects, both acute and delayed:

Irritation. Pre-existing skin problems may be aggravated by prolonged or repeated contact. See section 11 for additional information.

4.3. Indication of any immediate medical attention and special treatment needed:

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media:

Suitable: Use water spray, ABC dry chemical, foam or carbon dioxide. Water or foam may cause frothing. Use water to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures.

Unsuitable: Do not use direct water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture:

Unusual fire/explosion hazards: Product is not considered a fire hazard, but will burn if ignited. Closed container may rupture (due to build up in pressure) when exposed to extreme heat.

SDS Name: Kalama* Vetimoss

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (10.6 Hazardous decomposition products) for additional information.

5.3. Advice for firefighters:

Wear self-contained breathing apparatus (SCBA) equipped with a full facepiece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations.

See section 9 for additional information.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures:

See Section 8 for recommendations on the use of personal protective equipment. If spilled in an enclosed area, ventilate. Eliminate ignition sources. Personal Protective Equipment must be worn.

6.2. Environmental precautions:

Do not flush liquid into public sewer, water systems or surface waters.

6.3. Methods and material for containment and cleaning up:

Contain by diking with sand, earth or other non-combustible material. Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse.

6.4. References to other sections:

See Section 8 for recommendations on the use of personal protection and Section 13 for waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling:

As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Provide eyewash fountains and safety showers in the work area.

7.2. Conditions for safe storage, including any incompatibilities:

Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning. Empty container contains residual product which may exhibit hazards of product.

7.3. Specific end use(s):

Further information concerning special risk management measures: see annex of this safety data sheet (exposure scenarios).

SECTION 8: Exposure controls / personal protection

8.1. Control parameters:

Occupational exposure limits (OEL):

<u>Chemical Name</u>	<u>EU OELV</u>	<u>EU IOELV</u>	<u>ACGIH - TWA/Ceiling</u>	<u>ACGIH - STEL</u>
2-tert-Butyl-1,4-dimethoxybenzene	N/E	N/E	N/E	N/E
<u>Chemical Name</u>	<u>UK WEL</u>	<u>Ireland OEL</u>		
2-tert-Butyl-1,4-dimethoxybenzene	N/E	N/E		

N/E=Not established (no exposure limits established for the listed substances for listed country/region/organization).

Predicted No Effect Concentration (PNECs):

2-tert-Butyl-1,4-dimethoxybenzene

<u>Compartment</u>	<u>PNEC</u>
Freshwater	2,51 µg/L
Freshwater sediment	0,426 mg/kg dw
Marine water	0,251 µg/L
Marine water sediment	0,0426 mg/kg dw
Intermittent releases	25,1 µg/L
Soil	0,0837 mg/kg dw

SDS Name: Kalama* Vetimoss

Compartment

STP

Oral

PNEC

3 mg/L

No potential for bioaccumulation

N/E=Not established; N/A=Not applicable (not required); bw=body weight; dw=dry weight; ww=wet weight.

DNEL: no hazard identified.

8.2. Exposure controls:

Appropriate engineering controls: Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.

Individual protection measures, such as personal protective equipment:

Eye/face protection: Safety glasses or goggles required.

Hand protection: Avoid skin contact when mixing or handling the material by wearing impervious and chemical resistant gloves. In case of prolonged immersion or frequently repeated contact, gloves with breakthrough times greater than 480 minutes (protection class 6) are recommended. For brief contact or splash applications, gloves with breakthrough times of 30 minutes or greater are recommended (protection class 2 or greater). Suggested material for protective gloves: PVC (polyvinyl chloride). The protective gloves to be used must comply with the specifications of the Regulation (EU) 2016/425 and the resultant standard EN 374. Suitability and durability of a glove is dependent on usage (e.g. frequency and duration of contact, other chemicals which may be handled, chemical resistance of glove material and dexterity). Always seek advice of the glove supplier as to the most suitable glove material.

Skin and body protection: Use good laboratory/workplace procedures including personal protective clothing: labcoat, safety glasses and protective gloves.

Respiratory protection: Respiratory protection is not needed with proper ventilation. Wear an approved respirator (e.g., an organic vapor respirator, a full face air purifying respirator for organic vapors, or a self-contained breathing apparatus) whenever exposure to aerosol, mist, spray, fume or vapor exceed the applicable exposure limit(s) of any chemical substance listed in this SDS. Organic vapor filter (Type A).

Further information: Eyewash fountains and safety showers are recommended in the work area.

Environmental exposure controls: See Sections 6 and 12.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties:

Physical state:	Liquid
Colour:	Colorless to light yellow
Odour:	Characteristic
Odour threshold:	Not Available
Melting point/Freezing point:	-20°C (-4°F) @ 101.3 kPa
Boiling point °C:	253 °C @ 101.3 kPa
Boiling point °F:	487 °F @ 101.3 kPa
Flammability:	Not flammable
Lower and upper explosion limit:	LEL: Not Available UEL: Not Available
Flash point:	111 °C (232 °F) EU A.9 closed cup
Auto-ignition temperature:	396°C (745°F) @ 1013 hPa
Decomposition temperature:	Not Available
pH:	Not Available
Kinematic viscosity:	Not Available
Solubility in water:	19.17 mg/L (20°C)
Partition coefficient n-octanol/water (log value):	4.4 (OECD 117)
Vapour pressure:	20 Pa @ 20°C
Density and/or relative density:	0.994-0.996 (20°C)
Relative vapour density:	Not Available
Particle characteristics:	Not Applicable
% Volatile by weight:	Not Available
VOC:	Not Available
Surface tension:	69.5 mN/m @ 20°C

Amounts specified are typical and do not represent a specification.

9.2. Other information:

Information with regard to physical hazard classes:

SDS Name: Kalama* Vetimoss

Explosive properties: Not explosive

Oxidising properties: Not oxidizing

Other safety characteristics:

Evaporation rate: Not Available

SECTION 10: Stability and reactivity

10.1. Reactivity:

None known.

10.2. Chemical stability:

This product is stable.

10.3. Possibility of hazardous reactions:

Hazardous polymerization will not occur.

10.4. Conditions to avoid:

Excessive heat and ignition sources.

10.5. Incompatible materials:

Avoid contact with strong oxidizing agents.

10.6. Hazardous decomposition products:

Carbon dioxide, carbon monoxide and hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Inhalation LC50</u>	<u>Species</u>	<u>Oral LD50</u>	<u>Species</u>	<u>Dermal LD50</u>	<u>Species</u>
2-tert-Butyl-1,4-dimethoxybenzene	N/E	N/E	>2000 mg/kg (OECD 423)	Rat/ adult female	N/E	N/E

Skin corrosion/irritation: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Skin irritation</u>	<u>Species</u>
2-tert-Butyl-1,4-dimethoxybenzene	Non-irritant (OECD 431 & 439)	In-Vitro

Serious eye damage/irritation: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Eye irritation</u>	<u>Species</u>
2-tert-Butyl-1,4-dimethoxybenzene	Non-irritant (OECD 438 & 492)	In-Vitro

Respiratory or skin sensitization: Not classified (based on available data, the classification criteria are not met).

<u>Chemical Name</u>	<u>Skin sensitisation</u>	<u>Species</u>
2-tert-Butyl-1,4-dimethoxybenzene	Non-sensitizer (Draize)	Human

Carcinogenicity: Not classified (no relevant information found).

Germ cell mutagenicity: Suspected of causing genetic defects - Category 2. 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE: In-vitro Mouse lymphoma assay (OECD 490): Negative in the absence of metabolic activation and positive in the presence of metabolic activation. In-vitro Ames (OECD 471) and in-vitro Micronucleus (OECD 487) tests: Negative with and without metabolic activation.

Reproductive toxicity: Not classified (based on available data, the classification criteria are not met). 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE: Reproductive toxicity, oral study in rats: NOAEL (no-observed adverse-effect-level) 450 mg/kg bw/day (OECD 422). Developmental toxicity oral study, rats: NOAEL, developmental toxicity=450 mg/kg bw/day (OECD 422).

Specific target organ toxicity (STOT) - single exposure: Not classified (no relevant information found).

Specific target organ toxicity (STOT) - repeated exposure: Not classified (based on available data, the classification criteria are not met). 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE: Repeated dose study, oral, rats (OECD 422): NOAEL (no-observed-adverse-effect-level)=150 mg/kg bw/day (male), 450 mg/kg bw/day (female) (systemic effects).

Aspiration hazard: Not classified (no relevant information found).

Other toxicity information: No additional information available.

Information on likely routes of exposure:

General: Caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure.

SDS Name: Kalama* Vetimoss

Eyes: May cause eye irritation.

Skin: Repeated or prolonged skin contact may cause irritation.

Inhalation: High airborne concentrations of vapors resulting from heating, misting or spraying may cause irritation of the respiratory tract and mucous membranes.

Ingestion: Ingestion may cause irritation.

11.2. Information on other hazards

Endocrine disrupting properties: No specific information available.

Other information: No additional information available.

SECTION 12: Ecological information

12.1. Toxicity:

<u>Chemical Name</u>	<u>Species</u>	<u>Acute</u>	<u>Acute</u>	<u>Chronic</u>
2-tert-Butyl-1,4-dimethoxybenzene	Fish	LC50 2.51 mg/L (96 hours) (geometric mean measured)	N/E	N/E
2-tert-Butyl-1,4-dimethoxybenzene	Invertebrates	EC50 2.7 mg/L (48 hours) (geometric mean measured)	N/E	N/E
2-tert-Butyl-1,4-dimethoxybenzene	Algae	EL50 22.04 mg/L (72 hours) (yield)	EL50 56.94 mg/L(72 hours) (growth rate)	NOELR 6.25 mg/L(72 hours) (growth rate)
2-tert-Butyl-1,4-dimethoxybenzene	Micro-organisms	NOEC 30 mg/L (3 hours) (OECD 209)		

12.2. Persistence and degradability:

<u>Chemical Name</u>	<u>Biodegradation</u>
2-tert-Butyl-1,4-dimethoxybenzene	Not readily biodegradable (OECD 301F)

12.3. Bioaccumulative potential:

<u>Chemical Name</u>	<u>Bioconcentration Factor (BCF)</u>	<u>Log Kow</u>
2-tert-Butyl-1,4-dimethoxybenzene	N/E	4.4 (OECD 117)

12.4. Mobility in soil:

<u>Chemical Name</u>	<u>Mobility in soil (Koc/Kow)</u>
2-tert-Butyl-1,4-dimethoxybenzene	1660 @ 20°C (OECD 121)

12.5. Results of PBT and vPvB assessment:

This product does not meet the PBT and vPvB classification criteria.

12.6. Endocrine disrupting properties:

No specific information available.

12.7. Other adverse effects:

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods:

Dispose of unused contents (incineration) in accordance with national and local regulations. Dispose of container in accordance with national and local regulations. Ensure the use of properly authorized waste management companies, where appropriate.

See Section 8 for recommendations on the use of personal protective equipment.

SECTION 14: Transport information

The information below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions.

14.1. UN number or ID number: UN3082

14.2. UN proper shipping name:

Environmentally hazardous substance, liquid, n.o.s. (2-tert-Butyl-1,4-dimethoxybenzene)

14.3. Transport hazard class(es):

SDS Name: Kalama* Vetimoss

U.S. DOT hazard class: N/A
Canada TDG hazard class: 9
Europe ADR/RID/ADN hazard class: 9
IMDG Code (ocean) hazard class: 9
ICAO/IATA (air) hazard class: 9

A "N/A" listing for the hazard class indicates the product is not regulated for transport by that regulation.

14.4. Packing group: III

14.5. Environmental hazards:

Marine pollutant: Marine Pollutant (IMDG code 2.9.3).

Hazardous substance (USA): Not Applicable

14.6. Special precautions for user:

Not Applicable

14.7. Maritime transport in bulk according to IMO instruments

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Europe REACH (EC) 1907/2006: Applicable components are registered, exempt or otherwise compliant. EU REACH is only relevant to substances either manufactured or imported into the EU. Emerald Kalama Chemical has met its obligations under the EU REACH regulation. EU REACH information regarding this product is provided for informational purposes only. Each Legal Entity may have differing EU REACH obligations, depending on their place in the supply chain. Emerald's compliance with EU REACH does not imply automatic coverage for Downstream Users located in the EU. For material manufactured outside of the EU, the importer of record must understand and meet their specific obligations under the regulation.

EU Authorizations and/or restrictions on use: Not Applicable

Other EU information: No Additional Information

National regulations: No Additional Information

Chemical inventories:

Regulation

	Status
Australian Inventory of Industrial Chemicals (AIIC):	Y
Canadian Domestic Substances List (DSL):	Y
Canadian Non-Domestic Substances List (NDSL):	N
China Inventory of Existing Chemical Substances (IECSC):	Y
European EC Inventory (EINECS, ELINCS, NLP):	Y
Japan Existing and New Chemical Substances (ENCS):	N
Japan Industrial Safety and Health Law (ISHL):	Y
Korean Existing and Evaluated Chemical Substances (KECL):	N
New Zealand Inventory of Chemicals (NZIoC):	Y
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Y
Taiwan Inventory of Existing Chemicals:	Y
U.S. Toxic Substances Control Act (TSCA) (Active):	Y

A "Y" listing indicates all intentionally added components are either listed or are otherwise compliant with the regulation. A "N" listing indicates that for one or more components: 1) there is no listing on the public inventory (or is not on the ACTIVE inventory for U.S. TSCA); 2) no information is available; or 3) the component has not been reviewed. A "Y" for New Zealand may mean that a qualified group standard may exist for the components in this product.

UK REACH: As the UK has formally left the European Union, EU REACH [(EC) 1907/2006] is no longer directly applicable within the UK. Please see UK REACH formatted SDS for information related to UK REACH compliance.

15.2. Chemical safety assessment:

A chemical safety assessment has been carried out for the substance or mixture.

SECTION 16: Other information

Hazard (H) Statements in the Composition section (Section 3):

H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

Reason for revision: Changes in Section(s): 1

Evaluation method for classification of mixtures: Not Applicable (substance)

Legend:

* : Trademark owned by Emerald Kalama Chemical, LLC.
ACGIH: American Conference of Governmental Industrial Hygienists

SDS Name: Kalama* Vetimoss

ATE: Acute toxicity estimate
EU OELV: European Union Occupational Exposure Limit Value
EU IOELV: European Union Indicative Occupational Exposure Limit Value
N/A: Not Applicable
N/E: None Established
SCL: Specific concentration limit
STEL: Short Term Exposure Limit
TWA: Time Weighted Average (exposure for 8-hour workday)

Users Responsibility/Disclaimer of Liability:

The information set forth herein is based on our current knowledge, and is intended to describe the product solely with respect to health, safety and the environment. As such, it must not be interpreted as a guarantee of any specific property of the product. As a result, the customer shall be solely responsible for deciding whether said information is suitable and beneficial.

Safety Data Sheet Preparer:
Product Compliance Department
Emerald Kalama Chemical, LLC
1499 SE Tech Center Place, Suite 300
Vancouver, WA 98683
United States

Annex

Exposure Scenarios

Substance information:

Name of substance: 2-tert-butyl-1,4-dimethoxybenzene.
EC# 244-216-5 / CAS# 21112-37-8.
REACH Registration number: 01-2120866299-37-0000

List of exposure scenarios:

- ES1: Formulation or re-packing.
- ES2: Formulation - Formulation of fragrance compounds
- ES3: Formulation - Formulation of fragranced end-products
- ES4: Use at industrial sites - Industrial end-use of washing and cleaning products
- ES5: Use by professional workers - Professional end-use of washing and cleaning products
- ES6: Use by professional workers - Professional use of polishes and wax blends
- ES7: Consumer use - Consumer end-use of washing and cleaning products.
- ES8: Consumer use - Consumer end-use of air care products
- ES9: Consumer use - Consumer end-use of biocides
- ES10: Consumer use - Consumer end-use of polishes and wax blends.
- ES11: Consumer use - Consumer end-use of cosmetics

General remarks:

The first tier environmental exposure assessments have at first instance been performed using EUSES v2.1.2 which is part of Chemical Safety Assessment and Reporting tool version 3.4 (CHESAR v3.4). Higher tier assessments have been performed if safe use was not demonstrated using first tier assessments. In these cases Specific Environmental Release Categories (SpERCs) have been used or release fractions have been defined according to the A&B-tables in Appendix 1 of the 2003 Technical Guidance Document on Risk Assessment (EU TGD 2003), Part II.

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

Reference: IFRA REACH Exposure scenarios for Fragrance Substances. Version 2.1/11 December 2012.

Exposure scenario (1): Formulation or re-packing

1. Exposure scenario (1)

Short title of the exposure scenario:

Formulation or re-packing

List of use descriptors:

Process category (PROC): PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC15
Environmental release category (ERC): ERC2, ERC3 (SpERC IFRA 2.1a.v1)

List of names of contributing worker scenarios and corresponding PROCs:

- PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.
- PROC7 Industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.
- PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.
- PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.
- PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.
- PROC15 Use as laboratory reagent. Use of substances at small scale laboratory (< 1 l or 1 kg present at workplace).

SDS Name: Kalama* Vetimoss

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

ERC3 Formulation into solid matrix.

SpERC IFRA 2.1(a): Formulation of fragrance compounds at large/medium sites.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see <http://www.cefic.org/Industry-support/Implementing-reach/Libraries/>.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,08 ton/day.

Maximum annual use at a site: 20 tons/year.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Industrial use.

Release fraction to air from process (initial release): 0,00025; (final release): 0,00025. Local release rate: 0,02 kg/day (SpERC IFRA 2.1a.v1).

Release fraction to wastewater from process (initial release): 0,00002; (final release): 0,00002. Local release rate: 0,0016 kg/day (SpERC IFRA 2.1a.v1)

Release fraction to soil from process (final release):

- ERC2: 0,0001.

- ERC3: 0,001.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,0000407 mg/L	0,016	
Freshwater sediment	0,00691 mg/kg dw	0,016	
Marine water	0,00000433 mg/L	0,017	
Marine water sediment	0,000735 mg/kg dw	0,017	
Soil	0,00395 mg/kg dw	0,047	
STP	0,000213 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (2): Formulation - Formulation of fragrance compounds

1. Exposure scenario (2)

Short title of the exposure scenario:

Formulation - Formulation of fragrance compounds

List of use descriptors:

Process category (PROC): PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC15

Environmental release category (ERC): ERC2 (SpERC IFRA 2.1a.v1)

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.
 PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition.

PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.

PROC15 Use as laboratory reagent. Use of substances at small scale laboratory (< 1 l or 1 kg present at workplace).

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

SpERC IFRA 2.1(a): Formulation of fragrance compounds at large/medium sites.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see <http://www.cefic.org/Industry-support/Implementing-reach/Libraries/>.

2. Conditions of use affecting exposure**2.1 Control of workers exposure****General:**

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure**General:**

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,08 ton/day.

Maximum annual use at a site: 20 tons/year.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:Flow rate of receiving surface water: >=18,000 m³/day (default).**Other given operational conditions affecting environmental exposure:**

Indoor use.

Industrial use.

Release fraction to air from process (initial release): 0,00025; (final release): 0,00025. Local release rate: 0,02 kg/day (SpERC IFRA 2.1a.v1).

Release fraction to wastewater from process (initial release): 0,00002; (final release): 0,00002. Local release rate: 0,0016 kg/day (SpERC IFRA 2.1a.v1)

Release fraction to soil from process (final release): 0,0001.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m³/day (standard town).**Conditions and measures related to external treatment of waste for disposal:**

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,0000407 mg/L	0,016	
Freshwater sediment	0,00691 mg/kg dw	0,016	
Marine water	0,00000433 mg/L	0,017	

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Marine water sediment	0,000735 mg/kg dw	0,017	
Soil	0,00395 mg/kg dw	0,047	
STP	0,000213 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (3): Formulation - Formulation of fragranced end-products

1. Exposure scenario (3)

Short title of the exposure scenario:

Formulation - Formulation of fragranced end-products

List of use descriptors:

Process category (PROC): PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

Environmental release category (ERC): ERC2 (SpERC AISE 2.1g.v2).

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition.

PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.

PROC14 Tableting, compression, extrusion, pelletisation, granulation. This covers processing of mixtures and/or substances into a defined shape for further use.

PROC15 Use as laboratory reagent. Use of substances at small scale in laboratories (less than or equal to 1 l or 1 kg present at workplace).

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

SpERC AISE 2.1g.v2: Formulation of liquid Detergents/Maintenance Products: Low Viscosity (large site).

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see <http://www.cefic.org/Industry-support/Implementing-reach/Libraries/>.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,08 ton/day.

Maximum annual use at a site: 20 tons/year.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m³/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Industrial use.

Release fraction to air from process (initial release): 0,0; (final release): 0,0. Local release rate: 0 kg/day (EU TGD (2003) Table A2).

Release fraction to wastewater from process (initial release): 0,0001; (final release): 0,0001. Local release rate: 0,008 kg/day (EU TGD 2003 Table A2).

Release fraction to soil from process (final release): 0,0 (EU TGD 2003 Table A2).

Type of process: Substance applied in aqueous process solution with negligible volatilization.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

SDS Name: Kalama* Vetimoss

Process efficiency: Process optimized for highly efficient use of raw materials (very minimal environmental release).

Equipment cleaning: Equipment cleaning with minimized emissions to wastewater.

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

General good practice: Trained staff, spill protection including waste reuse.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000126 mg/L	0,05	
Freshwater sediment	0,021 mg/kg dw	0,05	
Marine water	0,0000128 mg/L	0,051	
Marine water sediment	0,00218 mg/kg dw	0,051	
Soil	0,019 mg/kg dw	0,232	
STP	0,00107 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (4): Use at industrial sites - Industrial end-use of washing and cleaning products

1. Exposure scenario (4)

Short title of the exposure scenario:

Use at industrial sites - Industrial end-use of washing and cleaning products

List of use descriptors:

Product category (PC): PC35

Process category (PROC): PROC2, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

Environmental release category (ERC): ERC4

List of names of contributing worker scenarios and corresponding PROCs:

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC4 Chemical production where opportunity for exposure arises.

PROC7 Industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.

PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.

PROC13 Treatment of articles by dipping and pouring.

Name of contributing environmental scenario and corresponding ERCs:

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article).

Further explanations:

PC35 Washing and cleaning products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

SDS Name: Kalama* Vetimoss

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,00000275 ton/day.

Maximum annual use at a site: 5 tons/year.

Frequency and duration of use:

Emission days: <=220 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Industrial use.

Indoor use.

Release fraction to air from process (initial release): 1.00; (final release): 1.00. Local release rate: 0,00275 kg/day.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,05.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0.072 mg/kg dw	0,857	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (5): Use by professional workers - Professional end-use of washing and cleaning products

1. Exposure scenario (5)

Short title of the exposure scenario:

Use by professional workers - Professional end-use of washing and cleaning products

List of use descriptors:

Product category (PC): PC35

Process category (PROC): PROC2, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

Environmental release category (ERC): ERC8a, ERC8d

List of names of contributing worker scenarios and corresponding PROCs:

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC4 Chemical production where opportunity for exposure arises.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging.

PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.

PROC11 Non industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

PROC13 Treatment of articles by dipping and pouring.

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor).

Further explanations:

PC35 Washing and cleaning products.

SDS Name: Kalama* Vetimoss

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor/Outdoor use.

Professional use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release):

- ERC8a: 0,00.

- ERC8d: 0,20.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0,00669 mg/kg dw	0,08	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (6): Use by professional workers - Professional use of polishes and wax blends

1. Exposure scenario (6)

Short title of the exposure scenario:

Use by professional workers - Professional use of polishes and wax blends

List of use descriptors:

Product category (PC): PC31

Process category (PROC): PROC2, PROC8a, PROC10, PROC11

Environmental release category (ERC): ERC8a

List of names of contributing worker scenarios and corresponding PROCs:

SDS Name: Kalama* Vetimoss

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.

PROC11 Non industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

Further explanations:

PC31 Polishes and wax blends.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Professional use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

<u>Effect/Compartment</u>	<u>Exposure estimate/PEC</u>	<u>RCR</u>	<u>Notes</u>
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0,00669 mg/kg dw	0,08	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (7): Consumer use - Consumer end-use of washing and cleaning products**1. Exposure scenario (7)****Short title of the exposure scenario:**

Consumer use - Consumer end-use of washing and cleaning products

List of use descriptors:

Product category (PC): PC35

Environmental release category (ERC): ERC8a, ERC8d

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor).

Further explanations:

PC35 Washing and cleaning products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure**2.1 Control of consumer exposure****General:**

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure**General:**

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:Flow rate of receiving surface water: >=18,000 m³/day (default).**Other given operational conditions affecting environmental exposure:**

Indoor/Outdoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release):

- ERC8a: 0,00.

- ERC8d: 0,20.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m³/day (standard town).**Conditions and measures related to external treatment of waste for disposal:**

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0,00669 mg/kg dw	0,08	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES**Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define

SDS Name: Kalama* Vetimoss

appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (8): Consumer use - Consumer end-use of air care products

1. Exposure scenario (8)

Short title of the exposure scenario:

Consumer use - Consumer end-use of air care products

List of use descriptors:

Product category (PC): PC3

Environmental release category (ERC): ERC8a

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

Further explanations:

PC3 Air care products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of consumer exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0,00669 mg/kg dw	0,08	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define

SDS Name: Kalama* Vetimoss

appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (9): Consumer use - Consumer end-use of biocides

1. Exposure scenario (9)

Short title of the exposure scenario:

Consumer use - Consumer end-use of biocides

List of use descriptors:

Product category (PC): PC8

Environmental release category (ERC): ERC8a, ERC8d

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor).

Further explanations:

PC8 Biocidal products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of consumer exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m³/day (default).

Other given operational conditions affecting environmental exposure:

Indoor/Outdoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release):

- ERC8a: 0,00.

- ERC8d: 0,20.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m³/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0,00669 mg/kg dw	0,08	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES**Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (10): Consumer use - Consumer end-use of polishes and wax blends**1. Exposure scenario (10)****Short title of the exposure scenario:**

Consumer use - Consumer end-use of polishes and wax blends

List of use descriptors:

Product category (PC): PC31

Environmental release category (ERC): ERC8a

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

Further explanations:

PC31 Polishes and wax blends.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure**2.1 Control of consumer exposure****General:**

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure**General:**

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0,00669 mg/kg dw	0,08	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES**Environment**

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (11): Consumer use - Consumer end-use of cosmetics**1. Exposure scenario (11)****Short title of the exposure scenario:**

Consumer use - Consumer end-use of cosmetics

List of use descriptors:

Product category (PC): PC39

Environmental release category (ERC): ERC8a

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

Further explanations:

PC39 Cosmetics, personal care products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure**2.1 Control of consumer exposure****General:**

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure**General:**

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	Notes
Freshwater	0,000056 mg/L	0,022	
Freshwater sediment	0,0095 mg/kg dw	0,022	
Marine water	0,00000586 mg/L	0,023	
Marine water sediment	0,000994 mg/kg dw	0,023	
Soil	0,00669 mg/kg dw	0,08	
STP	0,000366 mg/L	<0,01	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.
