Safety Data Sheet according to UK REACH Regulations SI 2020/1577



Revision date: 1/20/2022 Supercedes: 10/18/2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier:

Product trade name: Kalama* Vetimoss

Company product number: VETIMOSS

UK REACH registration number: UK-01-3834687072-8-0001
Substance name: 2-tert-Butyl-1,4-dimethoxybenzene

Substance identification number: EC 244-216-5

Other means of identification: 32186; Benzene, 2-(1,1-dimethylethyl)-1,4-dimethoxy-

1.2. Relevant identified uses of the substance or mixture and uses advised against:

Uses: Fragrance ingredient. Industrial applications. Professional applications.

Consumer applications. See Annex for covered uses.

Uses advised against: None identified

1.3. Details of the supplier of the safety data sheet:

Manufacturer/Supplier: Emerald Kalama Chemical Limited

Dans Road

Widnes, Cheshire WA8 0RF

United Kingdom

Telephone: +44 (0) 151 423 8000

For further information about this SDS: Email: product.compliance@emeraldmaterials.com

1.4. Emergency telephone number:

ChemTel (24 hours): 1-800-255-3924 (USA); +1-813-248-0585 (outside USA).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture:

Product classification according to GB CLP as amended:

Germ Cell Mutagenicity, category 2, H341

Hazardous to the aquatic environment, Chronic, category 2, H411

See Section 2.2 for full text of H (Hazard) statements.

2.2. Label elements:

Product labeling according to GB CLP as amended:

Hazard pictogram(s):





Signal word:

Warning

Hazard statements:

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P201 Obtain special instructions before use.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P391 Collect spillage.

Supplemental information: No Additional Information

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS) - Annex III and GB CLP Guidance on Labelling and Packaging. Regulations in individual countries/regions may determine which statements are required on the product label. See product label for specifics.

2.3. Other hazards:

PBT/vPvB criteria: This product does not meet the PBT and vPvB classification criteria.

Other hazards: No Additional Information

See Section 11 for toxicological information.

SECTION 3: Composition/information on ingredients

3.1. Substance:

CAS-No. **Chemical Name** Weight% Classification **H Statements** 0021112-37-8 2-tert-Butyl-1,4-dimethoxybenzene 99-100 Aquatic Chronic 2- Muta. 2 H341-411 **UK REACH Registration No.** CAS-No. **Chemical Name** Weight% **EC/List Number** 0021112-37-8 2-tert-Butyl-1,4-dimethoxybenzene 99-100 UK-01-3834687072-8-0001 244-216-5

See Section 16 for full text of H (Hazard) statements.

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

SECTION 4: First aid measures

4.1. Description of first aid measures:

General: If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician/get medical attention.

Eye contact: Immediately flush eyes with plenty of clean water for an extended time, not less than fifteen (15) minutes. Flush longer if there is any indication of residual chemical in the eye. Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. If eye irritation persists: Get medical advice/attention.

Skin contact: Immediately remove contaminated clothing and shoes. Wash the affected area with plenty of soap and water until no evidence of the chemical remains (at least 15-20 minutes). Launder clothing before reuse. If skin irritation occurs: Get medical advice/attention.

Inhalation: If affected, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse out the mouth with water. Get medical attention immediately.

Protection of first aid responders: Wear proper personal protective clothing and equipment.

4.2. Most important symptoms and effects, both acute and delayed:

Irritation. Pre-existing skin problems may be aggravated by prolonged or repeated contact. See section 11 for additional information.

4.3. Indication of any immediate medical attention and special treatment needed:

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media:

Suitable: Use water spray, ABC dry chemical, foam or carbon dioxide. Water or foam may cause frothing. Use water to keep fire-exposed containers cool. Water spray may be used to flush spills away from exposures.

Unsuitable: Do not use direct water stream. May spread fire.

5.2. Special hazards arising from the substance or mixture:

Unusual fire/explosion hazards: Product is not considered a fire hazard, but will burn if ignited. Closed container may rupture (due to build up in pressure) when exposed to extreme heat.

Hazardous combustion products: Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See section 10 (10.6 Hazardous decomposition products) for additional information.

5.3. Advice for firefighters:

Wear self-contained breathing apparatus (SCBA) equipped with a full facepiece and operated in a pressure-demand mode (or other positive pressure mode) and approved protective clothing. Personnel without suitable respiratory protection must leave the area to prevent significant exposure to hazardous gases from combustion, burning or decomposition. In an enclosed or poorly ventilated area, wear SCBA during cleanup immediately after a fire as well as during the attack phase of firefighting operations.

See section 9 for additional information.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures:

See Section 8 for recommendations on the use of personal protective equipment. If spilled in an enclosed area, ventilate. Eliminate ignition sources. Personal Protective Equipment must be worn.

6.2. Environmental precautions:

Do not flush liquid into public sewer, water systems or surface waters.

6.3. Methods and material for containment and cleaning up:

Contain by diking with sand, earth or other non-combustible material. Wear proper personal protective clothing and equipment. Absorb spill with an inert material. Place into labeled, closed container; store in safe location to await disposal. Change contaminated clothing and launder before reuse.

6.4. References to other sections:

See Section 8 for recommendations on the use of personal protection and Section 13 for waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling:

As with any chemical product, use good laboratory/workplace procedures. Do not cut, puncture, or weld on or near the container. Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities. Use under well-ventilated conditions. Avoid eye and skin contact. Avoid inhalation of aerosol, mist, spray, fume or vapor. Avoid drinking, tasting, swallowing or ingesting this product. Wash contaminated clothing before reuse. Provide eyewash fountains and safety showers in the work area.

7.2. Conditions for safe storage, including any incompatibilities:

Store cool and dry, under well-ventilated conditions. Store this material away from incompatible substances (see section 10). Do not store in open, unlabeled or mislabeled containers. Keep container closed when not in use. Do not reuse empty container without commercial cleaning or reconditioning. Empty container contains residual product which may exhibit hazards of product.

7.3. Specific end use(s):

Further information concerning special risk management measures: see annex of this safety data sheet (exposure scenarios).

SECTION 8: Exposure controls / personal protection

8.1. Control parameters:

Occupational exposure limits (OEL):

<u>Chemical Name</u> <u>ACGIH - TWA/Ceiling</u> <u>ACGIH - STEL</u>

2-tert-Butyl-1,4-dimethoxybenzene N/E N/E

 $N/E=Not\ established\ (no\ exposure\ limits\ established\ for\ the\ listed\ substances\ for\ listed\ country/region/organization).$

Predicted No Effect Concentration (PNECs):

2-tert-Butyl-1,4-dimethoxybenzene

Compartment **PNEC** Freshwater 2,51 µg/L Freshwater sediment 0,426 mg/kg dw Marine water $0,251 \mu g/L$ Marine water sediment 0,0426 mg/kg dw Intermittent releases 25,1 µg/L Soil 0,0837 mg/kg dw STP 3 mg/L

Oral No potential for bioaccumulation

 $N/E=Not\ established;\ N/A=Not\ applicable\ (not\ required);\ bw=body\ weight;\ dw=dry\ weight;\ ww=wet\ weight.$

DNEL: no hazard identified.

8.2. Exposure controls:

Appropriate engineering controls: Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.

Individual protection measures, such as personal protective equipment:

Eye/face protection: Safety glasses or goggles required.

Hand protection: Avoid skin contact when mixing or handling the material by wearing impervious and chemical resistant gloves. In case of prolonged immersion or frequently repeated contact, gloves with breakthrough times greater than 480 minutes (protection class 6) are recommended. For brief contact or splash applications, gloves with breakthrough times of 30 minutes or greater are recommended (protection class 2 or greater). The protective gloves to be used must comply with the specifications of the standard EN 374. Suitability and durability of a glove is dependent on usage (e.g. frequency and duration of contact, other chemicals which may be handled, chemical resistance of glove material and dexterity). Always seek advice of the glove supplier as to the most suitable glove material.

Skin and body protection: Use good laboratory/workplace procedures including personal protective clothing: labcoat, safety glasses and protective gloves.

Respiratory protection: Respiratory protection is not needed with proper ventilation. Wear an approved respirator (e.g., an organic vapor respirator, a full face air purifying respirator for organic vapors, or a self-contained breathing apparatus) whenever exposure to aerosol, mist, spray, fume or vapor exceed the applicable exposure limit(s) of any chemical substance listed in this SDS. Organic vapor filter (Type A).

Further information: Eyewash fountains and safety showers are recommended in the work area.

Environmental exposure controls: See Sections 6 and 12.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties:

Appearance: Liquid. Colorless to light yellow

Odour:CharacteristicOdour threshold:Not AvailablepH:Not Available

Melting point/Freezing point:-20°C (-4°F) @ 101.3 kPaInitial boiling point and boiling range °C:253 °C @ 101.3 kPaInitial boiling point and boiling range °F:487 °F @ 101.3 kPa

Flash point: 111 °C (232 °F) EU A.9 closed cup

Evaporation rate: Not Available

Flammability (solid, gas):

Upper/lower flammability or explosive limits:

Not Applicable (liquid)

LFL/LEL: Not Available

UFL/UEL: Not Available

Vapour pressure:20 Pa @ 20°CVapour density:Not AvailableRelative density:0.994-0.996 (20°C)Solubility in water:19.17 mg/L (20°C)Partition coefficient (n-octanol/water):4.4 (OECD 117)

Autoignition temperature: 396°C (745°F) @ 1013 hPa

Decomposition temperature:Not AvailableViscosity:Not AvailableExplosive properties:Not explosiveOxidising properties:Not oxidizing% Volatile By weight:Not AvailableVOC:Not AvailableSurface tension:69.5 mN/m @ 20°C

9.2. Other information:

Amounts specified are typical and do not represent a specification.

SECTION 10: Stability and reactivity

10.1. Reactivity:

None known.

10.2. Chemical stability:

This product is stable.

10.3. Possibility of hazardous reactions:

Hazardous polymerization will not occur.

10.4. Conditions to avoid:

Excessive heat and ignition sources.

10.5. Incompatible materials:

Avoid contact with strong oxidizing agents.

10.6. Hazardous decomposition products:

Carbon dioxide, carbon monoxide and hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects:

Information on likely routes of exposure:

General: Caution must be exercised through the prudent use of protective equipment and handling procedures to minimize exposure.

Eyes: May cause eye irritation.

Skin: Repeated or prolonged skin contact may cause irritation.

Inhalation: High airborne concentrations of vapors resulting from heating, misting or spraying may cause irritation of the respiratory tract and mucous membranes.

Ingestion: Ingestion may cause irritation.

Acute toxicity information: Not classified (based on available data, the classification criteria are not met).

Chemical NameInhalation LC50SpeciesOral LD50SpeciesDermal LD50Species2-tert-Butyl-1,4-dimethoxybenzeneN/EN/E>2000 mg/kg (OECDRat/ adultN/EN/E

Skin corrosion/irritation: Not classified (based on available data, the classification criteria are not met).

 Chemical Name
 Skin irritation
 Species

 2-tert-Butyl-1,4-dimethoxybenzene
 Non-irritant (OECD 431 & 439)
 In-Vitro

Serious eye damage/irritation: Not classified (based on available data, the classification criteria are not met).

 Chemical Name
 Eye irritation
 Species

 2-tert-Butyl-1,4-dimethoxybenzene
 Non-irritant (OECD 438 & 492)
 In-Vitro

Respiratory or skin sensitization: Not classified (based on available data, the classification criteria are not met).

 Chemical Name
 Skin sensitisation
 Species

 2-tert-Butyl-1,4-dimethoxybenzene
 Non-sensitizer (Draize)
 Human

Carcinogenicity: Not classified (no relevant information found).

Germ cell mutagenicity: Suspected of causing genetic defects - Category 2. 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE: Invitro Mouse lymphoma assay (OECD 490): Negative in the absence of metabolic activation and positive in the presence of metabolic activation. In-vitro Ames (OECD 471) and in-vitro Micronucleus (OECD 487) tests: Negative with and without metabolic activation.

Reproductive toxicity: Not classified (based on available data, the classification criteria are not met). 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE: Reproductive toxicity, oral study in rats: NOAEL (no-observed adverse-effect-level) 450 mg/kg bw/day (OECD 422). Developmental toxicity oral study, rats: NOAEL, developmental toxicity=450 mg/kg bw/day (OECD 422).

Specific target organ toxicity (STOT) - single exposure: Not classified (no relevant information found).

Specific target organ toxicity (STOT) - repeated exposure: Not classified (based on available data, the classification criteria are not met). 2-TERT-BUTYL-1,4-DIMETHOXYBENZENE: Repeated dose study, oral, rats (OECD 422): NOAEL (no-observed-adverse-effect-level)=150 mg/kg bw/day (male), 450 mg/kg bw/day (female) (systemic effects).

Aspiration hazard: Not classified (no relevant information found).

Other toxicity information: No additional information available.

SECTION 12: Ecological information

12.1. Toxicity:

Chemical Name Species Chronic Acute LC50 2.51 mg/L (96 hours) 2-tert-Butyl-1,4-dimethoxybenzene N/E N/E (geometric mean measured) Invertebrates EC50 2.7 mg/L (48 hours) N/E 2-tert-Butyl-1,4-dimethoxybenzene N/E

(geometric mean measured) 2-tert-Butyl-1,4-dimethoxybenzene EL50 22.04 mg/L (72 hours) (yield) EL50 56.94 mg/L(72 hours) NOELR 6.25 mg/L(72 hours) Algae (growth rate) (growth rate)

2-tert-Butyl-1,4-dimethoxybenzene Micro-organisms NOEC 30 mg/L (3 hours) (OECD

12.2. Persistence and degradability:

Chemical Name Biodegradation

Not readily biodegradable (OECD 301F) 2-tert-Butyl-1,4-dimethoxybenzene

12.3. Bioaccumulative potential:

Chemical Name Bioconcentration Factor (BCF) Log Kow 4.4 (OECD 117)

2-tert-Butyl-1,4-dimethoxybenzene

12.4. Mobility in soil:

Mobility in soil (Koc/Kow) **Chemical Name** 2-tert-Butyl-1,4-dimethoxybenzene 1660 @ 20°C (OECD 121)

12.5. Results of PBT and vPvB assessment:

This product does not meet the PBT and vPvB classification criteria.

12.6. Other adverse effects:

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods:

Dispose of unused contents (incineration) in accordance with national and local regulations. Dispose of container in accordance with national and local regulations. Ensure the use of properly authorized waste management companies, where appropriate.

See Section 8 for recommendations on the use of personal protective equipment.

SECTION 14: Transport information

The information below is provided to assist in documentation. It may supplement the information on the package. The package in your possession may carry a different version of the label depending on the date of manufacture. Depending on inner packaging quantities and packaging instructions, it may be subject to specific regulatory exceptions.

14.1. UN number: UN3082

14.2. UN proper shipping name:

Environmentally hazardous substance, liquid, n.o.s. (2-tert-Butyl-1,4-dimethoxybenzene)

14.3. Transport hazard class(es):

U.S. DOT hazard class: N/A Canada TDG hazard class: 9 Europe ADR/RID hazard class: 9 IMDG Code (ocean) hazard class: 9 ICAO/IATA (air) hazard class: 9

A "N/A" listing for the hazard class indicates the product is not regulated for transport by that regulation.

14.4. Packing group: III

14.5. Environmental hazards:

Marine pollutant: Marine Pollutant (IMDG code 2.9.3).

Hazardous substance (USA): Not Applicable

14.6. Special precautions for user:

Not Applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code:

Not Applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

STATUTORY INSTRUMENTS 2020 No. 1577, The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 [UK REACH]: Applicable components have been registered, are exempt or otherwise compliant. UK REACH is only relevant to substances either manufactured or imported into the UK. Emerald Kalama Chemical has met its obligations under the UK REACH regulation. UK REACH information regarding this product is provided for informational purposes only. Each Legal Entity may have differing UK REACH obligations, depending on their place in the supply chain. Emerald's compliance with UK REACH does not imply automatic coverage for Downstream Users located in the UK. For material manufactured outside of the UK, the importer of record must understand and meet their specific obligations under the regulation.

UK Authorizations and/or restrictions on use: Not Applicable

Other UK information: No Additional Information

Chemical inventories:

Regulation	<u>Status</u>
Australian Inventory of Industrial Chemicals (AIIC):	Υ
Canadian Domestic Substances List (DSL):	Υ
Canadian Non-Domestic Substances List (NDSL):	N
China Inventory of Existing Chemical Substances (IECSC):	Υ
European EC Inventory (EINECS, ELINCS, NLP):	Υ
Japan Existing and New Chemical Substances (ENCS):	N
Japan Industrial Safety and Health Law (ISHL):	Υ
Korean Existing and Evaluated Chemical Substances (KECL):	N
New Zealand Inventory of Chemicals (NZIoC):	Υ
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Υ
Taiwan Inventory of Existing Chemicals:	Υ
U.S. Toxic Substances Control Act (TSCA) (Active):	Υ

A "Y" listing indicates all intentionally added components are either listed or are otherwise compliant with the regulation. A "N" listing indicates that for one or more components: 1) there is no listing on the public inventory (or is not on the ACTIVE inventory for U.S. TSCA); 2) no information is available; or 3) the component has not been reviewed. A "Y" for New Zealand may mean that a qualified group standard may exist for the components in this product.

Europe REACH (EC) 1907/2006: Applicable components are registered, exempt or otherwise compliant. EU REACH is only relevant to substances either manufactured or imported into the EU. Emerald Kalama Chemical has met its obligations under the EU REACH regulation. EU REACH information regarding this product is provided for informational purposes only. Each Legal Entity may have differing EU REACH obligations, depending on their place in the supply chain. Emerald's compliance with EU REACH does not imply automatic coverage for Downstream Users located in the EU. For material manufactured outside of the EU, the importer of record must understand and meet their specific obligations under the regulation.

15.2. Chemical safety assessment:

A chemical safety assessment has been carried out for the substance or mixture consistent with the EU REACH regulation.

SECTION 16: Other information

Hazard (H) Statements in the Composition section (Section 3):

H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

Reason for revision: Changes in Section(s): 1

Evaulation method For classification Of mixtures: Not Applicable (substance)

Legend:

*: Trademark owned by Emerald Kalama Chemical, LLC.

ACGIH: American Conference of Governmental Industrial Hygienists

ATE: Acute toxicity estimate

N/A: Not Applicable N/E: None Established

STEL: Short Term Exposure Limit

TWA: Time Weighted Average (exposure for 8-hour workday)

UK WEL: United Kingdom Workplace Exposure Limits

Users Responsibility/Disclaimer of Liability:

The information set forth herein is based on our current knowledge, and is intended to describe the product solely with respect to health, safety and the environment. As such, it must not be interpreted as a guarantee of any specific property of the product. As a result, the customer shall be solely responsible for deciding whether said information is suitable and beneficial.

Safety Data Sheet Preparer: Product Compliance Department Emerald Kalama Chemical, LLC

1499 SE Tech Center Place, Suite 300

Vancouver, WA 98683

United States

Annex

Exposure Scenarios

Substance information:

Name of substance: 2-tert-butyl-1,4-dimethoxybenzene.

EC# 244-216-5 / CAS# 21112-37-8.

UK REACH Registration number: UK-01-3834687072-8-0001 EU REACH Registration number: 01-2120866299-37-0000

List of exposure scenarios:

ES1: Formulation or re-packing.

ES2: Formulation - Formulation of fragrance compounds

ES3: Formulation - Formulation of fragranced end-products

ES4: Use at industrial sites - Industrial end-use of washing and cleaning products

ES5: Use by professional workers - Professional end-use of washing and cleaning products

ES6: Use by professional workers - Professional use of polishes and wax blends

ES7: Consumer use - Consumer end-use of washing and cleaning products.

ES8: Consumer use - Consumer end-use of air care products

ES9: Consumer use - Consumer end-use of biocides

ES10: Consumer use - Consumer end-use of polishes and wax blends.

ES11: Consumer use - Consumer end-use of cosmetics

General remarks:

The first tier environmental exposure assessments have at first instance been performed using EUSES v2.1.2 which is part of Chemical Safety Assessment and Reporting tool version 3.4 (CHESAR v3.4). Higher tier assessments have been performed if safe use was not demonstrated using first tier assessments. In these cases Specific Environmental Release Categories (SpERCs) have been used or release fractions have been defined according to the A&B-tables in Appendix 1 of the 2003 Technical Guidance Document on Risk Assessment (EU TGD 2003), Part II.

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

Reference: IFRA REACH Exposure scenarios for Fragrance Substances. Version 2.1/11 December 2012.

Exposure scenario (1): Formulation or re-packing

1. Exposure scenario (1)

Short title of the exposure scenario:

Formulation or re-packing

List of use descriptors:

Process category (PROC): PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC15

Environmental release category (ERC): ERC2, ERC3 (SpERC IFRA 2.1a.v1)

List of names of contributing worker scenarios and corresponding PROCs:

PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.

PROC7 Industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging. PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.

PROC15 Use as laboratory reagent. Use of substances at small scale laboratory (< 1 l or 1 kg present at workplace).

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

ERC3 Formulation into solid matrix.

SpERC IFRA 2.1(a): Formulation of fragrance compounds at large/medium sites.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see http://www.cefic.org/Industry-support/Implementing-reach/Libraries/.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,08 ton/day. Maximum annual use at a site: 20 tons/year.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default)

Other given operational conditions affecting environmental exposure:

Indoor use.

Industrial use

Release fraction to air from process (initial release): 0,00025; (final release): 0,00025. Local release rate: 0,02 kg/day (SpERC IFRA 2.1a.v1). Release fraction to wastewater from process (initial release): 0,00002; (final release): 0,00002. Local release rate: 0,0016 kg/day (SpERC IFRA 2.1a.v1)

Release fraction to soil from process (final release):

- ERC2: 0,0001.
- ERC3: 0,001.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default)

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

0407 mg/L 91 mg/kg dw	0,016 0.016	
91 mg/kg dw	0.016	
	0,010	
00433 mg/L	0,017	
1735 mg/kg dw	0,017	
95 mg/kg dw	0,047	
	<0.01	-
	95 mg/kg dw	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (2): Formulation - Formulation of fragrance compounds

1. Exposure scenario (2)

Short title of the exposure scenario:

Formulation - Formulation of fragrance compounds

List of use descriptors:

Process category (PROC): PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC15

Environmental release category (ERC): ERC2 (SpERC IFRA 2.1a.v1)

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition.

PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging. PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.

PROC15 Use as laboratory reagent. Use of substances at small scale laboratory (< 1 l or 1 kg present at workplace).

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

SpERC IFRA 2.1(a): Formulation of fragrance compounds at large/medium sites.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see http://www.cefic.org/Industry-support/Implementing-reach/Libraries/.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,08 ton/day. Maximum annual use at a site: 20 tons/year.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default)

Other given operational conditions affecting environmental exposure:

Indoor use.

Industrial use.

Release fraction to air from process (initial release): 0,00025; (final release): 0,00025. Local release rate: 0,02 kg/day (SpERC IFRA 2.1a.v1). Release fraction to wastewater from process (initial release): 0,00002; (final release): 0,00002. Local release rate: 0,0016 kg/day (SpERC IFRA 2.1a.v1)

Release fraction to soil from process (final release): 0,0001.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	<u>Notes</u>	
Freshwater	0,0000407 mg/L	0,016		
Freshwater sediment	0,00691 mg/kg dw	0,016		
Marine water	0,00000433 mg/L	0,017		
Marine water sediment	0,000735 mg/kg dw	0,017		
Soil	0,00395 mg/kg dw	0,047		
STP	0,000213 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (3): Formulation - Formulation of fragranced end-products

1. Exposure scenario (3)

Short title of the exposure scenario:

Formulation - Formulation of fragranced end-products

List of use descriptors:

Process category (PROC): PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 Environmental release category (ERC): ERC2 (SpERC AISE 2.1g.v2).

List of names of contributing worker scenarios and corresponding PROCs:

PROC1 Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC3 Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition.

PROC5 Mixing or blending in batch processes. Covers mixing or blending of solid or liquid materials in the context of manufacturing or formulating sectors, as well as upon end use.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging. PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing). Filling lines specifically designed to both capture vapour and aerosol emissions and minimise spillage.

PROC14 Tabletting, compression, extrusion, pelletisation, granulation. This covers processing of mixtures and/or substances into a defined shape for further use.

PROC15 Use as laboratory reagent. Use of substances at small scale in laboratories (less than or equal to 1 l or 1 kg present at workplace).

Name of contributing environmental scenario and corresponding ERCs:

ERC2 Formulation into mixture.

SpERC AISE 2.1g.v2: Formulation of liquid Detergents/Maintenance Products: Low Viscosity (large site).

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf). For further information on CEFIC (The European Chemical Industry Council) Specific Environmental Release Categories (SpERCs), see http://www.cefic.org/Industry-support/Implementing-reach/Libraries/.

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,08 ton/day.

Maximum annual use at a site: 20 tons/year.

Frequency and duration of use:

Emission days: <=250 days/year.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Industrial use.

Release fraction to air from process (initial release): 0,0; (final release): 0,0. Local release rate: 0 kg/day (EU TGD (2003) Table A2).

Release fraction to wastewater from process (initial release): 0,0001; (final release): 0,0001. Local release rate: 0,008 kg/day (EU TGD 2003 Table A2).

Release fraction to soil from process (final release): 0,0 (EU TGD 2003 Table A2).

Type of process: Substance applied in aqueous process solution with negligible volatilization.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Process efficiency: Process optimized for highly efficient use of raw materials (very minimal environmental release).

Equipment cleaning: Equipment cleaning with minimized emissions to wastewater.

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

General good practice: Trained staff, spill protection including waste reuse.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR_	Notes
Freshwater	0,000126 mg/L	0,05	
Freshwater sediment	0,021 mg/kg dw	0,05	

Effect/Compartment	Exposure estimate/PEC	RCR	<u>Notes</u>	_
Marine water	0,0000128 mg/L	0,051		
Marine water sediment	0,00218 mg/kg dw	0,051		
Soil	0,019 mg/kg dw	0,232		
STP	0,00107 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (4): Use at industrial sites - Industrial end-use of washing and cleaning products

1. Exposure scenario (4)

Short title of the exposure scenario:

Use at industrial sites - Industrial end-use of washing and cleaning products

List of use descriptors:

Product category (PC): PC35

Process category (PROC): PROC2, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13

Environmental release category (ERC): ERC4

List of names of contributing worker scenarios and corresponding PROCs:

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC4 Chemical production where opportunity for exposure arises.

PROC7 Industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging. PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.

PROC13 Treatment of articles by dipping and pouring.

Name of contributing environmental scenario and corresponding ERCs:

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Further explanations:

PC35 Washing and cleaning products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Maximum daily use at a site: 0,00000275 ton/day.

Maximum annual use at a site: 5 tons/year.

Frequency and duration of use:

Emission days: <=220 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Industrial use.

Indoor use.

Release fraction to air from process (initial release): 1.00; (final release): 1.00. Local release rate: 0,00275 kg/day.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,05.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default)

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	<u>RCR</u>	<u>Notes</u>	
Freshwater	0,000056 mg/L	0,022		
Freshwater sediment	0,0095 mg/kg dw	0,022		
Marine water	0,00000586 mg/L	0,023		
Marine water sediment	0,000994 mg/kg dw	0,023		
Soil	0.072 mg/kg dw	0,857		
STP	0,000366 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (5): Use by professional workers - Professional end-use of washing and cleaning products

1. Exposure scenario (5)

Short title of the exposure scenario:

Use by professional workers - Professional end-use of washing and cleaning products

List of use descriptors:

Product category (PC): PC35

Process category (PROC): PROC2, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

Environmental release category (ERC): ERC8a, ERC8d

List of names of contributing worker scenarios and corresponding PROCs:

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC4 Chemical production where opportunity for exposure arises.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities. Transfer includes loading, filling, dumping, bagging. PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.

PROC11 Non industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

PROC13 Treatment of articles by dipping and pouring.

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor).

Further explanations:

PC35 Washing and cleaning products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor/Outdoor use.

Professional use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release):

- ERC8a: 0,00.

- ERC8d: 0,20.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	<u>Notes</u>	
Freshwater	0,000056 mg/L	0,022		
Freshwater sediment	0,0095 mg/kg dw	0,022		
Marine water	0,00000586 mg/L	0,023		
Marine water sediment	0,000994 mg/kg dw	0,023		
Soil	0,00669 mg/kg dw	0,08		
STP	0,000366 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (6): Use by professional workers - Professional use of polishes and wax blends

1. Exposure scenario (6)

Short title of the exposure scenario:

Use by professional workers - Professional use of polishes and wax blends

List of use descriptors:

Product category (PC): PC31

Process category (PROC): PROC2, PROC8a, PROC10, PROC11

Environmental release category (ERC): ERC8a

List of names of contributing worker scenarios and corresponding PROCs:

PROC2 Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions.

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities. Transfer includes loading, filling, dumping, bagging and weighing.

PROC10 Roller application or brushing. This includes application of paints, coatings, removers, adhesives or cleaning agents to surfaces with potential exposure arising from splashes.

PROC11 Non industrial spraying. Air dispersive techniques i.e. dispersion into air (= atomization) by e.g. pressurized air, hydraulic pressure or centrifugation, applicable for liquids and powders.

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

Further explanations:

PC31 Polishes and wax blends.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of workers exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default)

Other given operational conditions affecting environmental exposure:

Indoor use.

Professional use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	<u>RCR</u>	<u>Notes</u>	
Freshwater	0,000056 mg/L	0,022		
Freshwater sediment	0,0095 mg/kg dw	0,022		
Marine water	0,00000586 mg/L	0,023		
Marine water sediment	0,000994 mg/kg dw	0,023		
Soil	0,00669 mg/kg dw	0,08		
STP	0,000366 mg/L	<0,01	·	

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (7): Consumer use - Consumer end-use of washing and cleaning products

1. Exposure scenario (7)

Short title of the exposure scenario:

Consumer use - Consumer end-use of washing and cleaning products

List of use descriptors:

Product category (PC): PC35

Environmental release category (ERC): ERC8a, ERC8d

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Further explanations:

PC35 Washing and cleaning products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of consumer exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day.

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default)

Other given operational conditions affecting environmental exposure:

Indoor/Outdoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release):

- ERC8a: 0,00.
- ERC8d: 0,20.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default)

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	<u>RCR</u>	<u>Notes</u>	
Freshwater	0,000056 mg/L	0,022		
Freshwater sediment	0,0095 mg/kg dw	0,022		
Marine water	0,00000586 mg/L	0,023		
Marine water sediment	0,000994 mg/kg dw	0,023		
Soil	0,00669 mg/kg dw	0,08		
STP	0,000366 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (8): Consumer use - Consumer end-use of air care products

1. Exposure scenario (8)

Short title of the exposure scenario:

Consumer use - Consumer end-use of air care products

List of use descriptors:

Product category (PC): PC3

Environmental release category (ERC): ERC8a

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

Further explanations:

PC3 Air care products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of consumer exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default)

Other given operational conditions affecting environmental exposure:

Indoor use

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%)

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	<u>Notes</u>	
Freshwater	0,000056 mg/L	0,022		
Freshwater sediment	0,0095 mg/kg dw	0,022		
Marine water	0,00000586 mg/L	0,023		
Marine water sediment	0,000994 mg/kg dw	0,023		
Soil	0,00669 mg/kg dw	0,08		
STP	0,000366 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (9): Consumer use - Consumer end-use of biocides

1. Exposure scenario (9)

Short title of the exposure scenario:

Consumer use - Consumer end-use of biocides

List of use descriptors:

Product category (PC): PC8

Environmental release category (ERC): ERC8a, ERC8d

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Further explanations:

PC8 Biocidal products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of consumer exposure

General

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default)

Other given operational conditions affecting environmental exposure:

Indoor/Outdoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release):

- ERC8a: 0,00.
- ERC8d: 0,20.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town).

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	<u>RCR</u>	<u>Notes</u>	
Freshwater	0,000056 mg/L	0,022		
Freshwater sediment	0,0095 mg/kg dw	0,022		
Marine water	0,0000586 mg/L	0,023		
Marine water sediment	0,000994 mg/kg dw	0,023		
Soil	0,00669 mg/kg dw	0,08		
STP	0,000366 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (10): Consumer use - Consumer end-use of polishes and wax blends

1. Exposure scenario (10)

Short title of the exposure scenario:

Consumer use - Consumer end-use of polishes and wax blends

List of use descriptors:

Product category (PC): PC31

Environmental release category (ERC): ERC8a

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

Further explanations:

PC31 Polishes and wax blends.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of consumer exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and

therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18,000 m3/day (default)

Other given operational conditions affecting environmental exposure:

Indoor use

Consumer use

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Exposure estimate/PEC	RCR	<u>Notes</u>	
0,000056 mg/L	0,022		
0,0095 mg/kg dw	0,022		
0,00000586 mg/L	0,023		
0,000994 mg/kg dw	0,023		
0,00669 mg/kg dw	0,08		
0,000366 mg/L	<0,01		
	0,000056 mg/L 0,0095 mg/kg dw 0,00000586 mg/L 0,000994 mg/kg dw 0,00669 mg/kg dw	0,000056 mg/L 0,022 0,0095 mg/kg dw 0,022 0,00000586 mg/L 0,023 0,000994 mg/kg dw 0,023 0,00669 mg/kg dw 0,08	0,000056 mg/L 0,022 0,0095 mg/kg dw 0,022 0,00000586 mg/L 0,023 0,000994 mg/kg dw 0,023 0,00669 mg/kg dw 0,08

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.

Exposure scenario (11): Consumer use - Consumer end-use of cosmetics

1. Exposure scenario (11)

Short title of the exposure scenario:

Consumer use - Consumer end-use of cosmetics

List of use descriptors:

Product category (PC): PC39

Environmental réleasé category (ERC): ERC8a

Name of contributing environmental scenario and corresponding ERCs:

ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor).

Further explanations:

PC39 Cosmetics, personal care products.

For further information on standardized use descriptors see the European Chemical Agency (ECHA) Guidance on information requirements and chemical safety assessment, Chapter R.12: Use descriptor system (http://guidance.echa.europa.eu/docs/guidance_document/information_requirements_r12_en.pdf).

2. Conditions of use affecting exposure

2.1 Control of consumer exposure

General:

Data from acute toxicity studies as well as available repeated dose toxicity (oral route) studies demonstrate the lack of adverse effects subsequent to exposure to the substance tested. As no effects were demonstrated, the data are not appropriate for DNEL derivation and therefore human exposure assessments have not been conducted.

2.2 Control of environmental exposure

General:

All risk management measures utilised must also comply with all relevant local regulations.

Product characteristics:

Physical state: liquid.

Vapour pressure: 20 Pa at 20 °C

Amounts used:

Daily wide dispersive use: 0,00000275 tons/day

Frequency and duration of use:

Emission days: <=365 days/year.

Wide dispersive use.

Environmental factors not influenced by risk management:

Flow rate of receiving surface water: >=18000 m3/day (default).

Other given operational conditions affecting environmental exposure:

Indoor use.

Consumer use.

Release fraction to air from process (initial release): 1,00; (final release): 1,00.

Release fraction to wastewater from process (initial release): 1,00; (final release): 1,00. Local release rate: 0,00275 kg/day.

Release fraction to soil from process (final release): 0,0.

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Dry sludge application to agricultural soil: Yes (default).

Conditions and measures related to municipal sewage treatment plant:

Municipal Sewage Treatment Plant (STP): Yes (Efficiency=73,35%).

Size of municipal sewage system/treatment plant: >=2000 m3/day (standard town)

Conditions and measures related to external treatment of waste for disposal:

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste:

External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice:

All risk management measures utilised must also comply with all relevant local regulations.

3. Exposure estimation and reference to its source

Assessment method-Environment: CHESAR v3.4 - EUSES v2.1.2.

Environment

Effect/Compartment	Exposure estimate/PEC	RCR	<u>Notes</u>	
Freshwater	0,000056 mg/L	0,022		
Freshwater sediment	0,0095 mg/kg dw	0,022		
Marine water	0,00000586 mg/L	0,023		
Marine water sediment	0,000994 mg/kg dw	0,023		
Soil	0,00669 mg/kg dw	0,08		
STP	0,000366 mg/L	<0,01		

RCR=Risk characterization ratio (PEC/PNEC or Exposure estimate/DNEL); PEC=Predicted environmental concentration.

4. Guidance to the Downstream User to evaluate whether he works inside the boundaries set by the ES

Environment:

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.