DATA SHEET

Chopped Strands CS 7928





Polymer	<b>PA</b> CS 7928 <sup>*</sup> is used for reinforcement of a wide range of polyamide grades.		
Product Description	High strand integrity		
	Excellent free-flowing properties		
	Suitable for bulk transport and pneumatic conveyance		
	High mechanical strength in a wide range of polyamide grades		
Technical	Fiber Diameter (nom.)	11 µm	
Characteristics	Av. Fiber Length (nom.)	4,5 mm	
	Glass	E-Glass (DIN 1259)	
	Size	Polymeric size containing silane	
	Moisture content	≤ 0,05 wt%	
	Size content	approx. 0,75 wt%	
	(Original data ex works)		
Packaging	Big Bag, Octabin, PE Bags (see detailed information on next page)		
Storage	The glass fiber should be stored in a dry place, preferably at room tempera- ture and 50 - 70 % relative humidity.		
Contact	For further information please contact:		
	Mail	glassfiber@lanxess.com	
	Phone	+49 (0)221 8885 7275	

DATA SHEET



## Packaging Information CS 7928

Big Bag, recyclable		Telescope Octabin	
Net Weight	1000 kg / 1100 kg	Net Weight	1000 kg
<b>Dimensions Bag</b>	1030 x 1030 x 1400 mm	Dimensions Octabin	1086 x 1086 x 1550 mm
<b>Dimensions Pallet</b>	1140 x 1140 mm (CP3)	Dimensions Pallet	1100 x 1100 mm
Packaging Code	BD00 - FA100T / FW 110T	Packaging Code	ZR10 TELESCOPE
Bottom unloading through discharge spout		Pallet with hole	450 x 450 mm
LANXESS			
Big Bag, recyclable		PE Bags	
Net Weight	800 kg	Net Weight Bag	20 kg
Dimensions Bag	870 x 870 x 1400 mm	Net Weight Pallet	20 kg x 50 = 1000 kg
<b>Dimensions Pallet</b>	1000 x 1200 mm (CP1)	Dimensions Pallet	1300 x 1100 mm (CP7)
Packaging Code	BD05 – FA800H	Packaging Code	SD 00 – BA 100E
Bottom unloading through discharge spout			10 layers per pallet
LAXES			

## Disclaimer

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

Values

Unless specified to the contrary, the values given have been established on standardized test. The figures should be regarded as guide values only and not as binding minimum values.

© = LANXESS Deutschland GmbH | HPM Business Unit | all rights reserved www.glassfiber.lanxess.com Page 2 of 2 | Edition 14.12.2020