DATA SHEET

Chopped Strands CS 7929

CS 7929		
Polymer	PA, PPO	
	CS 7929 [*] is used for reinforcen It can also be used for reinforce	nent of a wide range of polyamide grades. ement of PPO.
Product Description	High strand integrity	
	Excellent mechanical strength	
Technical	Fiber Diameter (nom.)	14 µm
Characteristics	Av. Fiber Length (nom.)	4,5 mm
	Glass	E-Glass (DIN 1259)
	Size	Polymeric size containing silane
	Moisture content	≤ 0,05 wt%
	Size content	approx. 0,75 wt%
	(Original data ex works)	
Packaging	Big Bag, (see detailed informat	ion on next page)
Storage	The glass fiber should be store ture and 50 - 70 % relative hum	d in a dry place, preferably at room tempera- nidity.
Contact	For further information please of	contact:

Mail

Phone





glassfiber@lanxess.com

+49 (0)221 8885 7275

DATA SHEET



Packaging Information CS 7929

Big Bag, recyclable Big Bag, recyclable Net Weight 1000 kg Dimensions Bag 1030 x 1030 x 1400 mm Dimensions Pallet 1140 x 1140 mm (CP3) Packaging Code BD00 - FA100T Bottom unloading thrush discharge spout Bottom unloading through discharge spout Formula Softom unloading thrush discharge spout Image: Soft Soft Soft Soft Soft Soft Soft Soft
Dimensions Bag 1030 x 1030 x 1400 mm Dimensions Bag. 1030 x 1030 x 1150 mm Dimensions Pallet 1140 x 1140 mm (CP3) Dimensions Pallet 1200 x 1000 mm (CP1) Packaging Code BD00 - FA100T Packaging Code BD05 - FA080T
Dimensions Pallet1140 x 1140 mm (CP3)Dimensions Pallet1200 x 1000 mm (CP1)Packaging CodeBD00 - FA100TPackaging CodeBD05 - FA080T
Packaging Code BD00 - FA100T Packaging Code BD05 - FA080T
Bottom unloading through discharge spout Bottom unloading through discharge spout Image: Spoin and Spoin a
LAXXESS LAXXESS

Disclaimer

Values

Unless specified to the contrary, the values given have been established on standardized test. The figures should be regarded as guide values only and not as binding minimum values.

© = LANXESS Deutschland GmbH | HPM Business Unit | all rights reserved www.glassfiber.lanxess.com Page 2 of 2 | Edition 14.12.2020

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.